



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
1	834	250834	≥40	≥3.7	≤2.7	≤8.60	≤34.5	1.0
2	8400	8400	≥180	≥3.7	≤8.2	≤8.20	≤40.0	3.5
3	912	300912	≥17	≥3.7	≤3.1	≤9.00	≤11.5	0.4
4	923	340923	≥40	≥3.7	≤3.4	≤9.30	≤23.0	0.9
5	937	300937	≥68	≥3.7	≤3	≤9.5	≤37.5	1.5
6		390937	≥95	≥3.7	≤3.9	≤8.80	≤37.0	2.0
7		390937L	≥80	≥3.7	≤3.9	≤9.5	≤37.5	1.7
8	1013	351013P	≥15	≥3.7	≤3.5	≤9.80	≤13.5	0.4
9		501013P	≥25	≥3.7	≤5	≤10.3	≤14	0.6
10	1018	251018	≥21	≥3.7	≤2.7	≤10.5	≤18.8	0.6
11		381018	≥35	≥3.7	≤4.0	≤10.8	≤18.5	0.8
12		381018P	≥25	≥3.7	≤3.8	≤11.0	≤18.5	0.6
13		401018	≥45	≥3.7	≤4.2	≤10.8	≤19.0	1.0
14		431018	≥45	≥3.7	≤4.4	≤10.5	≤18.5	1.0
15		521018G	≥55	≥3.7	≤5.3	≤10.5	≤17.7	1.2
16	1020	251020	≥25	≥3.7	≤2.7	≤10.8	≤20.8	0.6
17		281020P	≥25	≥3.7	≤2.8	≤10.8	≤20.5	0.6
18		301020	≥30	≥3.7	≤3.2	≤11.0	≤20.8	0.7
19		331020	≥40	≥3.7	≤3.4	≤11.0	≤20.5	0.9
20		351020	≥45	≥3.7	≤3.6	≤10.5	≤21.5	1.0
21		401020G	≥50	≥3.7	≤4.0	≤10.0	≤21.7	1.1
22		441020G	≥58	≥3.7	≤4.3	≤10.7	≤20.0	1.2
23	1024	321024	≥50	≥3.7	≤3.4	≤10.4	≤24.0	1.1
24		341024P	≥40	≥3.7	≤3.4	≤10.4	≤24.0	0.9
25		361024	≥55	≥3.7	≤3.6	≤10.4	≤24.0	1.2
26		541024	≥95	≥3.7	≤5.4	≤10.0	≤24.5	1.9
27	1025	371025	≥50	≥3.7	≤3.7	≤10.0	≤25.0	1.1
28	1027	301027G	≥45	≥3.7	≤3.0	≤10.3	≤28.2	1.0
29		501027	≥80	≥3.7	≤5.0	≤10.3	≤27.5	1.7
30	1028	341028G	≥60	≥3.7	≤3.3	≤9.80	≤28.0	1.3
31	1029	301029	≥60	≥3.7	≤2.95	≤10.0	≤29.5	1.3
32		411029	≥85	≥3.7	≤4.1	≤10.5	≤29.5	1.8
33	1030	301030	≥60	≥3.7	≤3.1	≤10.8	≤30.5	1.3
34		301030P	≥50	≥3.7	≤3	≤10.8	≤30.5	1.2
35		331030	≥70	≥3.7	≤3.4	≤10.8	≤30.5	1.5
36		351030P	≥65	≥3.7	≤3.7	≤10.8	≤30.5	1.4
37		381030	≥70	≥3.7	≤3.8	≤10.5	≤30.5	1.5
38		401030H	≥90	≥3.7	≤4.1	≤10.8	≤30.5	1.9

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
39	1030	421030	≥95	≥3.7	≤4.3	≤10.8	≤30.5	1.9
40		431030	≥90	≥3.7	≤4.6	≤10.8	≤30.5	1.9
41	1033	301033	≥70	≥3.7	≤3.1	≤10.3	≤33.0	1.5
42		441033	≥120	≥3.7	≤4.4	≤10.8	≤33.5	2.4
43	1035	251035	≥55	≥3.7	≤2.8	≤10.8	≤35.5	1.3
44		431035	≥110	≥3.7	≤4.3	≤10.5	≤35.5	2.2
45	1039	351039	≥110	≥3.7	≤3.5	≤10.8	≤39.5	2.3
46		401039	≥120	≥3.7	≤4.05	≤10.5	≤39.5	2.4
47	1040	701040	≥230	≥3.7	≤7	≤10	≤40.5	4.4
48	1045	471045	≥180	≥3.7	≤4.6	≤10.3	≤45.5	3.5
49	1048	301048	≥100	≥3.7	≤3.0	≤10.8	≤48.5	2.2
50		331048	≥120	≥3.7	≤3.3	≤10.5	≤48.5	2.5
51	1051	331051	≥140	≥3.7	≤3.3	≤10.1	≤51.0	2.9
52	1055	331055	≥120	≥3.7	≤3.5	≤10.5	≤55.5	2.5
53		401055	≥160	≥3.7	≤4.0	≤10.5	≤55.5	3.2
54	1058	371058	≥160	≥3.7	≤3.7	≤10.8	≤58.5	3.3
55	1114	371114	≥21.0	≥3.7	≤3.6	≤10.9	≤13.8	0.5
56	1116	411116	≥40	≥3.7	≤4.1	≤12	≤16.5	0.9
57	1120	381120P	≥45	≥3.7	≤4.0	≤11.5	≤20.5	1.0
58		381120	≥50	≥3.7	≤3.8	≤11.5	≤20.5	1.1
59		401120	≥55	≥3.7	≤4.1	≤11.5	≤20.5	1.2
60		491120	≥70	≥3.7	≤4.9	≤11.5	≤20.0	1.4
61	1123	601123	≥100	≥3.7	≤6.0	≤11.0	≤23.0	2.0
62	1124	231124	≥25	≥3.7	≤2.3	≤11.5	≤24.5	0.7
63		401124	≥80	≥3.7	≤4.15	≤11.3	≤25.0	1.7
64		451124	≥85	≥3.7	≤4.5	≤11.5	≤24.5	1.7
65		541124	≥95	≥3.7	≤5.4	≤11.5	≤24.5	1.9
66		581124	≥105	≥3.7	≤4.15	≤11.0	≤25.5	2.1
67	1126	721126	≥145	≥3.7	≤7.2	≤11.3	≤26.5	2.8
68	1132	341132	≥90	≥3.7	≤3.4	≤11.5	≤32.5	1.9
69		391132	≥110	≥3.7	≤3.95	≤12.0	≤32.5	2.2
70		401132P	≥100	≥3.7	≤4.2	≤11.8	≤32.5	2.1
71		491132	≥145	≥3.7	≤4.9	≤11.8	≤32.0	2.8
72	1135	401135G	≥110	≥3.7	≤4.0	≤12.0	≤32.5	2.2
73		401135	≥120	≥3.7	≤4.0	≤12.0	≤35.5	2.4
74	1141	631141P	≥185	≥3.7	≤6.3	≤11.5	≤41.5	3.6
75	1165	431165	≥250	≥3.7	≤4.5	≤11.2	≤65.5	4.9
76	1215	301215	≥25	≥3.7	≤3.2	≤12.5	≤15.5	0.6

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
77	1215	361215	≥40	≥3.7	≤3.6	≤12.5	≤15.5	0.9
78		401215H	≥40	≥3.7	≤4.0	≤12.5	≤15.5	0.9
79		451215	≥40	≥3.7	≤4.5	≤12.5	≤15.5	0.9
80		471215	≥45	≥3.7	≤4.7	≤12.0	≤15.5	1.0
81		501215	≥45	≥3.7	≤4.95	≤12.3	≤14.8	1.0
82		531215	≥48	≥3.7	≤5.3	≤12.5	≤15.5	1.0
83		581215	≥50	≥3.7	≤5.8	≤12.5	≤15.5	1.1
84	1216	401216	≥42	≥3.7	≤4.0	≤11.8	≤16.5	0.9
85		451216	≥45	≥3.7	≤4.4	≤11.0	≤16.5	1.0
86	1218	351218G	≥40	≥3.7	≤3.45	≤11.8	≤18.0	0.9
87		401218	≥50	≥3.7	≤4	≤12.0	≤18.0	1.1
88		481218P	≥50	≥3.7	≤4.8	≤12.0	≤18.5	1.1
89		501218G	≥60	≥3.7	≤4.95	≤11.8	≤18.0	1.3
90	1219	351219	≥45	≥3.7	≤3.6	≤12.5	≤19.0	1.0
91		401219	≥50	≥3.7	≤4.05	≤12.5	≤19.5	1.1
92		421219	≥55	≥3.7	≤4.2	≤12.3	≤19.5	1.2
93		431219	≥60	≥3.7	≤4.3	≤12.0	≤19.5	1.3
94		481219	≥70	≥3.7	≤4.9	≤12.5	≤19.5	1.5
95		551219P	≥60	≥3.7	≤5.5	≤12.5	≤19.5	1.3
96		551220P	≥65	≥3.7	≤5.5	≤12.5	≤19.5	1.4
97		581219	≥80	≥3.7	≤5.8	≤12.5	≤19.7	1.6
98		751219	≥100	≥3.7	≤7.5	≤12.5	≤19.7	2.0
99	1220	251220G	≥30	≥3.7	≤2.8	≤12.5	≤21.0	0.8
100		301220	≥40	≥3.7	≤3.1	≤12.5	≤21.0	0.9
101		351220G	≥52	≥3.7	≤3.6	≤12.5	≤20.5	1.1
102		401221	≥70	≥3.7	≤4.2	≤12.5	≤21.0	1.5
103		451220	≥70	≥3.7	≤4.5	≤12.5	≤21.0	1.5
104		481220	≥80	≥3.7	≤5.0	≤12.5	≤20.5	1.6
105		581220	≥95	≥3.7	≤5.8	≤12.5	≤20.5	1.9
106		601220	≥100	≥3.7	≤6.25	≤12.5	≤20.8	2.0
107		801220G	≥130	≥3.7	≤8.0	≤12.5	≤21.0	2.5
108	1221	401221	≥70	≥3.7	≤4.0	≤12.5	≤21.0	1.5
109		481221	≥90	≥3.7	≤4.8	≤12.5	≤21.5	1.8
110		501221P	≥75	≥3.7	≤5.0	≤12.2	≤21.0	1.5
111		651221	≥110	≥3.7	≤6.5	≤12.5	≤21.5	2.2
112	1222	281222	≥45	≥3.7	≤2.8	≤12.5	≤23.0	1.0
113		371222	≥70	≥3.7	≤3.65	≤12.3	≤23.0	1.5
114	1223	321223	≥60	≥3.7	≤3.2	≤12.5	≤23.5	1.3

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
115	1223	331223	≥65	≥3.7	≤3.3	≤12.3	≤23.5	1.4
116		381223	≥65	≥3.7	≤3.8	≤12.5	≤23.5	1.4
117		411223P	≥80	≥3.7	≤4.1	≤11.9	≤23.0	1.6
118		451223	≥85	≥3.7	≤4.5	≤12.5	≤23.5	1.7
119	1225	301225	≥50	≥3.7	≤3.0	≤12.5	≤25.5	1.1
120		371225	≥83	≥3.7	≤3.7	≤12.5	≤25.5	1.7
121		381225	≥90	≥3.7	≤4.0	≤12.5	≤25.5	1.8
122		421225	≥90	≥3.7	≤4.2	≤12.5	≤25.5	1.8
123		451225	≥100	≥3.7	≤4.6	≤12.5	≤25.5	2.0
124	1226	361226	≥75	≥3.7	≤3.5	≤12.0	≤25.5	1.6
125		551226G	≥120	≥3.7	≤5.4	≤12.2	≤27.0	2.4
126	1230	201230	≥30	≥3.7	≤2.7	≤12.5	≤30.5	0.8
127		351230	≥90	≥3.7	≤3.55	≤12	≤29.0	1.9
128		401230H	≥105	≥3.7	≤4.0	≤12.3	≤30.0	2.1
129		401230	≥110	≥3.7	≤4.0	≤12.8	≤30.3	2.2
130		431230	≥125	≥3.7	≤4.3	≤12.5	≤30.5	2.5
131		451230G	≥125	≥3.7	≤4.46	≤12.0	≤30.5	2.5
132		471230	≥138	≥3.7	≤4.7	≤12.5	≤30.5	2.7
133		481230	≥125	≥3.7	≤4.65	≤12.3	≤30.5	2.5
134		501230	≥130	≥3.7	≤5.0	≤12.5	≤30.5	2.6
135		531230G	≥140	≥3.7	≤5.3	≤12.5	≤30.5	2.8
136		601230	≥160	≥3.7	≤6.2	≤12.5	≤30.5	3.1
137	1235	251235	≥70	≥3.7	≤2.7	≤12.5	≤35.5	1.6
138		401235H	≥130	≥3.7	≤4.0	≤12.5	≤35.5	2.6
139		501235	≥150	≥3.7	≤5.0	≤12.5	≤35.0	3.0
140		551235	≥180	≥3.7	≤5.7	≤12.5	≤35.5	3.5
141		601235	≥200	≥3.7	≤6.0	≤12.5	≤35.5	3.8
142		651235	≥210	≥3.7	≤6.5	≤12.0	≤36.0	4.0
143	701235	≥220	≥3.7	≤7.0	≤12.5	≤35.5	4.2	
144	1240	501240	≥220	≥3.7	≤5.2	≤12.5	≤41.0	4.2
145		541240	≥200	≥3.7	≤5.4	≤12.5	≤40.5	3.9
146		701240	≥260	≥3.7	≤6.6	≤12.5	≤40.5	4.9
147		711240	≥260	≥3.7	≤7.1	≤12.5	≤41.0	4.9
148	1244	701244	≥320	≥3.7	≤6.9	≤12.4	≤44.3	6.0
149	1245	451245	≥200	≥3.7	≤4.7	≤12.5	≤45.5	3.9
150		501245P	≥230	≥3.7	≤5.3	≤12.5	≤46.0	4.4
151		551245	≥250	≥3.7	≤5.9	≤12.0	≤46.0	4.8
152		601245P	≥260	≥3.7	≤6.1	≤12.5	≤43.5	4.9

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
153	1245	601245	≥280	≥3.7	≤6.0	≤12.0	≤45.0	5.3
154		631245	≥280	≥3.7	≤6.3	≤12.5	≤45.5	5.3
155		701245	≥300	≥3.7	≤6.6	≤12.5	≤45.5	5.7
156	1248	651248	≥330	≥3.7	≤6.5	≤12.5	≤48.5	6.2
157	1259	501259HV	≥400	3.8	≤5.0	≤12.0	≤59.0	7.5
158	1265	601265G	≥450	≥3.7	≤6.15	≤12.3	≤65.0	8.4
159	1317	301317	≥40	≥3.7	≤3.5	≤12.5	≤16.0	0.9
160	1320	301320	≥50	≥3.7	≤3.2	≤13.5	≤20.0	1.1
161		361320	≥68	≥3.7	≤3.8	≤13.5	≤20.5	1.4
162		551320P	≥90	≥3.7	≤5.5	≤13.2	≤20.5	1.8
163		601320P	≥70	≥3.7	≤6	≤13.0	≤20.5	1.5
164	1324	461324	≥100	≥3.7	≤4.6	≤13.0	≤23.5	2.0
165	1341	301341	≥130	≥3.7	≤3.0	≤13.5	≤41.5	2.7
166	1350	451350	≥300	≥3.7	≤4.7	≤13.5	≤50.5	5.7
167		801350	≥500	≥3.7	≤8.2	≤13.7	≤50.5	9.2
168	1358	551358	≥400	≥3.7	≤5.5	≤13.5	≤58.5	7.5
169	1362	681362G	≥530	≥3.7	≤6.8	≤13.5	≤62.0	9.8
170	1416	451416	≥50	≥3.7	≤4.5	≤14.5	≤16.0	1.1
171	1417	501417	≥60	≥3.7	≤5.2	≤14.5	≤17.5	1.3
172		501417H	≥70	≥3.7	≤5.0	≤14.5	≤17.5	1.5
173		551417G	≥65	≥3.7	≤5.5	≤14.5	≤17.8	1.4
174		601417	≥70	≥3.7	≤6.0	≤14.5	≤17.8	1.5
175		811417	≥100	≥3.7	≤8.15	≤14.5	≤17.8	2.0
176	1419	251419	≥35	≥3.7	≤2.5	≤14.5	≤19.5	0.8
177		391419	≥65	≥3.7	≤3.9	≤14.5	≤19.5	1.4
178		501419	≥80	≥3.7	≤5.0	≤14.5	≤19.5	1.6
179		551419	≥100	≥3.7	≤5.5	≤14.5	≤19.5	2.0
180	1421	401421	≥80	≥3.7	≤4.1	≤14.0	≤22.0	1.7
181	1422	401422	≥80	≥3.7	≤4.0	≤14.5	≤22.5	1.7
182		451422P	≥70	≥3.7	≤4.6	≤14.5	≤22.5	1.5
183		451422	≥95	≥3.7	≤4.45	≤14.3	≤22.5	1.9
184		511422	≥110	≥3.7	≤5.1	≤14.5	≤22.5	2.2
185	1423	301423	≥65	≥3.7	≤3.0	≤14.5	≤23.1	1.4
186	1425	301425	≥80	≥3.7	≤3.0	≤14	≤25.0	1.7
187		341425	≥85	≥3.7	≤3.4	≤14	≤25.0	1.8
188		401425	≥100	≥3.7	≤4.1	≤14.3	≤25.0	2.0
189		501425	≥140	≥3.7	≤5.0	≤14.5	≤25.0	2.7
190	1426	301426	≥75	≥3.7	≤3.2	≤14.5	≤26.5	1.6

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
191	1426	331426	≥90	≥3.7	≤3.3	≤14.5	≤26.5	1.9
192	1427	421427	≥110	≥3.7	≤4.3	≤14.5	≤27.0	2.2
193	1428	301428	≥80	≥3.7	≤3.1	≤14.5	≤28.5	1.7
194		401428G	≥110	≥3.7	≤4.00	≤15.5	≤28.5	2.2
195		421428	≥120	≥3.7	≤4.2	≤14.8	≤28.8	2.4
196	1429	401429	≥130	≥3.7	≤4.2	≤14.5	≤29.5	2.6
197		701429	≥220	≥3.7	≤7.3	≤14.5	≤29.8	4.2
198	1430	401430	≥145	≥3.7	≤4.1	≤14.3	≤30.5	2.9
199		451430	≥150	≥3.7	≤4.6	≤14.5	≤30.5	3.0
200		501430	≥170	≥3.7	≤5.2	≤14.5	≤30.5	3.3
201		551430	≥180	≥3.7	≤5.5	≤14.3	≤30.5	3.5
202		601430P	≥150	≥3.7	≤6.0	≤14.5	≤30.8	3.0
203		651430	≥210	≥3.7	≤6.5	≤14.5	≤30.5	4.0
204	1435	351435	≥130	≥3.7	≤3.5	≤14.5	≤35.5	2.6
205		501435	≥200	≥3.7	≤5.0	≤14.5	≤35.5	3.9
206		631435	≥250	≥3.7	≤6.3	≤14.0	≤35.8	4.7
207		701435	≥300	≥3.7	≤7.15	≤14.5	≤35.5	5.6
208	1437	801437P	≥350	≥3.7	≤7.9	≤14.4	≤36.5	6.5
209	1439	281439	≥115	≥3.7	≤2.8	≤14.0	≤39.5	2.4
210		531439	≥260	≥3.7	≤5.5	≤14.3	≤39.5	4.9
211		701439	≥320	≥3.7	≤7.1	≤14.5	≤39.5	6.0
212	1440	401440	≥190	≥3.7	≤3.9	≤14.3	≤39.5	3.7
213	1442	451442	≥250	≥3.7	≤4.6	≤13.7	≤42.0	4.8
214		491442	≥250	≥3.7	≤4.9	≤14.5	≤42.5	4.8
215	1447	601447	≥350	≥3.7	≤6.0	≤14.0	≤47.5	6.6
216		751447G	≥450	≥3.7	≤7.5	≤14.0	≤47.0	8.3
217		901447	≥520	≥3.7	≤8.95	≤14.3	≤47.0	9.5
218	1450	701450	≥480	≥3.7	≤7.0	≤14.0	≤50.5	8.9
219	1452	651452	≥420	≥3.7	≤6.5	≤14.5	≤52.5	7.8
220		801452	≥500	≥3.7	≤8	≤14.5	≤52.5	9.2
221	1454	681454	≥450	≥3.7	≤6.8	≤14.5	≤54.5	8.4
222		801454	≥580	≥3.7	≤8.15	≤14.3	≤54.5	10.6
223	1458	451458F	≥155	≥3.7	≤4.5	≤13.5	≤58	3.2
224	1471	401471	≥360	≥3.7	≤4.0	≤14.5	≤71.5	6.9
225		661471	≥600	≥3.7	≤6.6	≤14.0	≤71.0	11.1
226	1515	201515	≥22	≥3.7	≤2.0	≤15.0	≤15.0	0.6
227		401515	≥50	≥3.7	≤4.2	≤15.5	≤15.5	1.1
228		401515HV	≥60	≥3.7	≤4.2	≤15.4	≤16.3	1.3

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
229	1515	661515	≥85	≥3.7	≤6.6	≤15.0	≤15.5	1.7
230	1517	231517	≥25	≥3.7	≤2.3	≤15.6	≤17.0	0.7
231	1518	531518	≥85	≥3.7	≤5.3	≤15.5	≤18.5	1.7
232		751518	≥130	≥3.7	≤7.5	≤15.5	≤18.5	2.5
233	1519	201519	≥1091	≥3.7	≤2.2	≤16.0	≤19.8	20.2
234	1520	301520	≥40	≥3.7	≤3.0	≤15.5	≤20.5	0.9
235		371520	≥65	≥3.7	≤3.7	≤15.2	≤20.5	1.4
236	1521	301521	≥75	≥3.7	≤3.0	≤15.85	≤21.5	1.5
237	1522	571522	≥210	≥3.7	≤8.7	≤15.5	≤22.5	4.0
238		851522	≥210	≥3.7	≤8.5	≤15.2	≤23.0	4.0
239	1524	301524	≥70	≥3.7	≤3.0	≤15.0	≤25.0	1.5
240		351524	≥90	≥3.7	≤3.5	≤15.5	≤24.0	1.9
241	1525	301525	≥80	≥3.7	≤3.2	≤15.3	≤25.5	1.7
242		321525	≥80	≥3.7	≤3.2	≤15.5	≤24.5	1.7
243		381525	≥90	≥3.7	≤3.6	≤15.3	≤24.5	1.9
244		401525	≥100	≥3.7	≤4.05	≤15.5	≤25.5	2.0
245	1528	301528	≥100	≥3.7	≤3.1	≤15.0	≤28.5	2.1
246		451528G	≥140	≥3.7	≤4.5	≤15.5	≤28.5	2.8
247		501528	≥150	≥3.7	≤5.0	≤15.2	≤28.5	2.9
248		561528	≥180	≥3.7	≤5.6	≤15.5	≤28.5	3.5
249		561528H	≥200	≥3.7	≤5.6	≤15.5	≤28.5	3.8
250		571528	≥190	≥3.7	≤5.65	≤15.3	≤28.5	3.7
251		601528PG	≥210	≥3.7	≤6.2	≤15.5	≤28.5	4.0
252		701528	≥200	≥3.7	≤7.0	≤15.5	≤28.5	3.8
253	1533	301533G	≥100	≥3.7	≤2.88	≤15.3	≤33.0	2.1
254		351533P	≥100	≥3.7	≤3.5	≤15.5	≤33.5	2.1
255		701533P	≥230	≥3.7	≤7.2	≤15.5	≤33.5	4.4
256	1537	501537	≥250	≥3.7	≤5.0	≤16.0	≤37.5	4.8
257		531537	≥260	≥3.7	≤5.3	≤15.5	≤37.8	4.9
258		571537	≥300	≥3.7	≤5.6	≤15.3	≤38.5	5.6
259		601537H	≥270	≥3.7	≤6.0	≤15.5	≤37.5	5.1
260		631537G	≥300	≥3.7	≤6.3	≤15.5	≤37.5	5.6
261		781537G	≥380	≥3.7	≤7.8	≤15.5	≤37.8	7.0
262	1547	441547	≥270	≥3.7	≤4.4	≤15.5	≤47.0	5.2
263	1550	301550	≥185	≥3.7	≤3.0	≤15.5	≤50.5	3.7
264		401550	≥280	≥3.7	≤4.2	≤15.5	≤50.5	5.4
265		501550P	≥300	≥3.7	≤5.0	≤15.0	≤50.0	5.7
266	1558	561558	≥530	≥3.7	≤5.6	≤15.5	≤58.5	9.8

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
267	1558	801558G	≥650	≥3.7	≤8.0	≤15.5	≤58.0	11.9
268	1572	361572	≥360	≥3.7	≤3.65	≤15.5	≤72.5	7.0
269		501572F	≥250	≥3.2	≤5	≤14.8	≤72.0	5.0
270	1575	451575	≥450	≥3.7	≤4.5	≤15.4	≤73.5	8.6
271		701575	≥800	≥3.7	≤7.0	≤15.5	≤75.5	14.7
272	1623	481623	≥120	≥3.7	≤4.5	≤16.3	≤23.50	2.0
273	1624	351624	≥90	≥3.7	≤3.5	≤16.5	≤24.5	1.9
274		481624	≥120	≥3.7	≤4.5	≤16.5	≤23.50	2.0
275		501624	≥120	≥3.7	5.1	≤16.5	≤23.5	2.4
276		801624G	≥200	≥3.7	≤8.2	≤16.2	≤23.0	3.8
277		801624HG	≥210	≥3.7	≤8.2	≤16.0	≤23.5	4.0
278		601622	≥160	≥3.7	≤6.0	≤16.2	≤22.5	3.1
279	1628	621628PG	≥210	≥3.7	≤6.2	≤15.5	≤28.5	4.0
280	1630	501630	≥230	≥3.7	≤5.2	≤16.5	≤31.0	4.4
281	1635	351635	≥140	≥3.7	≤3.5	≤16.5	≤35.5	2.8
282		451635	≥200	≥3.7	≤4.5	≤16.5	≤35.5	3.9
283		631635G	≥300	≥3.7	≤6.25	≤16.3	≤35.5	5.6
284		301643	≥175	≥3.7	≤3.0	≤16.0	≤43.5	3.5
285		361643	≥200	≥3.7	≤3.6	≤16.5	≤43.5	4.0
286	1643	501643	≥280	≥3.7	≤5.0	≤16.5	≤43.5	5.4
287		551643	≥330	≥3.7	≤5.7	≤16.5	≤43.5	6.2
288		751643	≥430	≥3.7	≤7.5	≤16.5	≤43.5	8.0
289		901643	≥560	≥3.7	≤8.95	≤16.3	≤44.0	10.2
290	1646	501646	≥300	≥3.7	≤5.0	≤16.5	≤46.5	5.7
291		541646	≥380	≥3.7	≤5.35	≤16.4	≤46.0	7.1
292		631646	≥430	≥3.7	≤6.3	≤16.8	≤46.5	8.0
293		651646	≥450	≥3.7	≤6.5	≤16.8	≤46.5	8.4
294		781646	≥550	≥3.7	≤7.8	≤16.8	≤46.5	10.1
295		851646	≥600	≥3.7	≤8.5	≤16.8	≤46.5	11.0
296		901646	≥630	≥3.7	≤9.0	≤16.8	≤46.5	11.5
297	1657	521657	≥420	≥3.7	≤5.2	≤16.8	≤57.0	7.9
298	1663	581663	≥530	≥3.7	≤5.8	≤16.5	≤63.5	9.9
299		601663	≥560	≥3.7	≤6.0	≤16.5	≤63.5	10.4
300	1670	741671	≥840	≥3.7	≤7.35	≤15.8	≤70.5	15.3
301		751671	≥840	≥3.7	≤7.5	≤15.8	≤70.5	15.3
302	1680	701680	≥750	≥3.7	≤6.9	≤16.0	≤80.0	13.8
303	1695	481695	≥740	≥3.7	≤4.9	≤16.5	≤95.5	13.8
304	1716	401716	≥60	≥3.7	≤4.0	≤17.0	≤16.0	1.3

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



2019 Lithium Polymer Cell Selection Guide

509 East Ellis Road, Norton Shores, MI 49441 U.S.A.

Toll Free No. 1-800-798-7740

ISO 13485

Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
305	1723	101723	≥300	≥3.7	≤10.2	≤17.5	≤24.5	5.6
306	1724	351724	≥115	≥3.7	≤3.5	≤17.5	≤24.5	2.3
307	1725	321725	≥100	≥3.7	≤3.2	≤17.1	≤25.5	2.1
308		381725	≥110	≥3.7	≤3.8	≤17.5	≤25.5	2.2
309		451725	≥120	≥3.7	≤4.5	≤17.5	≤25.5	2.4
310		501725	≥150	≥3.7	≤5.2	≤17.5	≤25.5	2.9
311		651725	≥220	≥3.7	≤6.5	≤17.5	≤25.5	4.2
312		681725P	≥220	≥3.7	≤6.8	≤17.5	≤25.5	4.2
313	1730	251730	≥95	≥3.7	≤2.7	≤17.5	≤30.5	2.0
314		301730	≥120	≥3.7	≤3.0	≤17.5	≤30.5	2.5
315		401730	≥160	≥3.7	≤4.1	≤17.5	≤30.5	3.2
316		451730	≥180	≥3.7	≤4.5	≤17.5	≤30.5	3.5
317		501730	≥200	≥3.7	≤5.0	≤17.3	≤30.5	3.9
318		551730	≥250	≥3.7	≤5.7	≤17.5	≤30.5	4.7
319		651730	≥280	≥3.7	≤6.7	≤17.5	≤30.5	5.3
320		751730	≥330	≥3.7	≤7.5	≤17.5	≤30.5	6.1
321		781730	≥350	≥3.7	≤7.8	≤17.5	≤31.0	6.5
322		801730	≥350	≥3.7	≤8.2	≤17.5	≤30.8	6.5
323	1735	491735	≥260	≥3.7	≤4.9	≤17.3	≤35.0	5.0
324		601735	≥300	≥3.7	≤6.0	≤17.0	≤35.0	5.6
325		801735	≥400	≥3.7	≤8.0	≤17.5	≤35.5	7.4
326	1736	471736	≥260	≥3.7	≤4.7	≤17.7	≤36.5	5.0
327		701736	≥350	≥3.7	≤6.9	≤16.9	≤34	6.5
328	1738	451738	≥250	≥3.7	≤4.5	≤17.5	≤37.5	4.8
329		501738HV	≥350	≥3.75	≤4.9	≤16.9	≤38.3	6.5
330		961738HG	≥530	≥3.7	≤9.6	≤17.3	≤39.5	9.7
331	1740	501740	≥320	≥3.7	≤5.0	≤17.5	≤41.0	6.1
332		681740	≥420	≥3.7	≤6.8	≤17.5	≤40.5	7.8
333		801740	≥470	≥3.7	≤8.0	≤17.2	≤40.8	8.7
334	1752	331752	≥260	≥3.7	≤3.3	≤17.5	≤52.5	5.1
335		351752G	≥280	≥3.7	≤3.5	≤17.5	≤53.5	5.5
336		381752	≥300	≥3.7	≤3.8	≤17.5	≤52.5	5.8
337		551752	≥450	≥3.7	≤5.5	≤17.5	≤52.5	8.4
338		601752	≥470	≥3.7	≤6.0	≤17.5	≤52.5	8.8
339		801752G	≥730	≥3.7	≤8.2	≤17.5	≤52.5	13.3
340	1756	621756	≥580	≥3.7	≤6.2	≤17.0	≤56.5	10.7
341	1760	671760HV	≥800	≥3.8	≤6.7	≤17.5	≤60.5	14.6
342		831760	≥890	≥3.7	≤8.2	≤17.6	≤60.5	16.2

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
343	1772	631772	≥800	≥3.7	≤6.3	≤17.5	≤72.5	14.7
344	1780	541780G	≥680	≥3.7	≤5.4	≤17.0	≤80.0	12.7
345	1818	301818	≥65	≥3.7	≤3	≤18.5	≤18.5	1.4
346		601818	≥135	≥3.7	≤6.0	≤18.0	≤18.5	2.6
347		801818	≥170	≥3.7	≤8.2	≤18.0	≤19.0	3.3
348	1823	611823	≥190	≥3.7	≤6.1	≤17.8	≤23.0	3.6
349	1828	501828	≥220	≥3.7	≤5.0	≤18.0	≤28.0	4.2
350	1832	501828	≥450	≥3.7	≤8.8	≤18.5	≤32.5	8.3
351	1834	401834G	≥200	≥3.7	≤4.0	≤18.2	≤34.0	3.9
352		451834	≥220	≥3.7	≤4.5	≤18.5	≤34.5	4.3
353		461834	≥230	≥3.7	≤4.75	≤18.5	≤34.5	4.4
354		481834	≥270	≥3.7	≤4.8	≤18.5	≤34	5.1
355		701834	≥380	≥3.7	≤7.1	≤18.5	≤34.5	7.1
356		101834	≥550	≥3.7	≤10.0	≤18.3	≤34.8	10.0
357	1837	651837	≥400	≥3.7	≤6.5	≤18	≤37.2	7.4
358		891837G	≥520	≥3.7	≤8.9	≤18.5	≤39.0	9.5
359		901837	≥520	≥3.7	≤8.9	≤18.0	≤37.5	9.5
360	1838	401838	≥240	≥3.7	≤4.0	≤18.3	≤39.5	4.7
361		551838	≥330	≥3.7	≤5.7	≤18.5	≤37.5	6.2
362	1841	751841	≥580	≥3.7	≤7.6	≤18.5	≤41.5	10.6
363		851841	≥610	≥3.7	≤8.5	≤18.5	≤41.5	11.1
364	1860	461860	≥480	≥3.7	≤4.6	≤18.5	≤60.5	9.0
365		631860	≥715	≥3.7	≤6.3	≤17.6	≤60.5	13.1
366	1866	501866	≥420	≥3.7	≤4.9	≤16.5	≤63.5	8.0
367	1885	451885	≥730	≥3.7	≤4.6	≤19.0	≤85.8	13.6
368		501885	≥900	≥3.7	≤5	≤18.5	≤85.5	16.6
369		571885	≥1000	≥3.7	≤5.7	≤18.8	≤86.0	18.4
370		801885	≥1500	≥3.7	≤8.0	≤18.8	≤86	27.1
371	1919	621919	≥150	≥3.7	≤6.2	≤19.8	≤21.5	2.9
372	1920	3619120	≥1000	≥3.7	≤3.6	≤20	≤120	18.8
373		381920	≥90	≥3.7	≤3.8	≤19.5	≤20.0	1.9
374		501920	≥145	≥3.7	≤5	≤19.5	≤20.5	2.8
375	1927	501927	≥210	≥3.7	≤5.0	≤19.5	≤27.5	4.0
376		801927	≥320	≥3.7	≤8.0	≤19.5	≤27.8	6.0
377	1938	321938G	≥200	≥3.7	≤3.2	≤19.7	≤40.0	4.0
378	1939	101939	≥650	≥3.7	≤10.0	≤19.8	≤39.0	11.8
379	1945	601945D	≥450	≥3.7	≤6	≤19.5	≤44.5	8.4
380	2018	362018HV	≥90	≥3.8	≤3.6	≤19.8	≤18.5	1.9

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**

Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
381	2018	402018	≥95	≥3.8	≤4.0	≤20.0	≤18.5	1.9
382	2020	302020	≥80	≥3.7	≤3.0	≤20.5	≤20.5	1.7
383		402020	≥120	≥3.7	≤4.2	≤20.5	≤20.5	2.4
384		482020	≥120	≥3.7	≤4.8	≤20.5	≤20.5	2.4
385		502020	≥150	≥3.7	≤5.2	≤20.5	≤20.5	2.9
386		602020	≥180	≥3.7	≤6.0	≤20.5	≤21.8	3.5
387		702020	≥200	≥3.7	≤7.0	≤20.5	≤20.5	3.8
388		2022	442022	≥150	≥3.7	≤4.4	≤20.5	≤22.5
389	762022		≥260	≥3.7	≤7.6	≤20.5	≤22.8	4.9
390	2023	302023	≥80	≥3.7	≤3.0	≤20.5	≤23.5	1.7
391		322023H	≥100	≥3.7	≤3.2	≤19.8	≤23.5	2.1
392		352023	≥115	≥3.7	≤3.4	≤19.8	≤23.5	2.3
393		382023	≥115	≥3.7	≤3.8	≤20.5	≤23.5	2.3
394		402023	≥125	≥3.7	≤4.2	≤20.5	≤23.5	2.5
395		422023	≥150	≥3.7	≤4.2	≤19.9	≤23.5	3.0
396		452023	≥150	≥3.7	≤4.5	≤20.5	≤23.5	3.0
397		472023	≥165	≥3.7	≤4.7	≤20.7	≤23.5	3.2
398		652023	≥240	≥3.7	≤6.6	≤20.5	≤23.5	4.6
399		752023G	≥270	≥3.7	≤7.5	≤20.5	≤23.7	5.1
400		802024	≥280	≥3.7	≤8.5	≤20.8	≤24.5	5.3
401	2023	802024	≥280	≥3.7	≤8	≤20.8	≤24.5	5.3
402	2025	252025	≥90	≥3.7	≤2.7	≤20.5	≤25.5	1.9
403		302025	≥100	≥3.7	≤3.0	≤20.5	≤25.5	2.1
404		352025	≥130	≥3.7	≤3.7	≤20.5	≤25.5	2.6
405		352025L	≥115	≥3.7	≤3.5	≤20.5	≤25.5	2.4
406		382025G	≥110	≥3.7	≤3.6	≤20.5	≤25.5	2.3
407		402025H	≥160	≥3.7	≤4.0	≤20.0	≤25.0	3.1
408		412025HV	≥175	≥3.7	≤4.1	≤19.9	≤23.5	3.4
409		432025	≥160	≥3.7	≤4.3	≤20.5	≤25.5	3.2
410		452025	≥165	≥3.7	≤4.5	≤20.5	≤25.5	3.2
411		482025	≥190	≥3.7	≤4.8	≤20	≤25.5	3.7
412		502025	≥210	≥3.7	≤5.0	≤20.5	≤25.8	4.0
413		532025	≥200	≥3.7	≤5.3	≤20.0	≤25.5	3.9
414		602025	≥240	≥3.7	≤6.2	≤20.5	≤25.5	4.6
415		702025	≥280	≥3.7	≤7.2	≤20.5	≤25.5	5.3
416		802025	≥320	≥3.7	≤8.0	≤20.5	≤25.5	6.0
417		902025P	≥300	≥3.7	≤9	≤20	≤20.5	5.6
418	2027	252027	≥85	≥3.7	≤2.6	≤20.0	≤25.5	1.8



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
419	2027	442027	≥190	≥3.7	≤4.4	≤20.5	≤27.5	3.7
420		522027HV	≥270	≥3.8	≤5.1	≤20.5	≤28.0	5.1
421		552027	≥250	≥3.7	≤5.4	≤20.2	≤27.5	4.8
422	2028	282028HG	≥125	≥3.7	≤2.8	≤20.5	≤28.5	2.6
423		402028G	≥170	≥3.7	≤4.0	≤21.0	≤29.5	3.4
424		502028	≥220	≥3.7	≤5.2	≤20.5	≤29.0	4.2
425		602028	≥270	≥3.7	≤6.2	≤19.8	≤28.0	5.1
426		752028	≥390	≥3.7	≤7.5	≤20	≤29	7.2
427		802028	≥390	≥3.7	≤8.0	≤20	≤20.8	7.2
428		952028	≥500	≥3.7	≤9.5	≤20.5	≤29.0	9.2
429	2030	252030G	≥100	≥3.7	≤2.8	≤20.5	≤30.0	2.1
430		302030	≥130	≥3.7	≤3.0	≤20.5	≤30.5	2.7
431		342030	≥160	≥3.7	≤3.4	≤19.8	≤28.5	3.2
432		352030	≥160	≥3.7	≤3.5	≤20.5	≤30.5	3.2
433		382030	≥190	≥3.7	≤3.8	≤20.3	≤30.5	3.7
434		402030H	≥200	≥3.7	≤4.1	≤20.3	≤30.5	3.9
435		452030	≥250	≥3.7	≤4.6	≤20.3	≤30.5	4.8
436		462030	≥220	≥3.7	≤4.6	≤20.5	≤30.5	4.3
437		482030G	≥240	≥3.7	≤4.8	≤20.5	≤30.5	4.6
438		502030	≥260	≥3.7	≤4.98	≤20.3	≤30.5	5.0
439		552030G	≥280	≥3.7	≤5.5	≤20.5	≤30.5	5.3
440		582030	≥300	≥3.7	≤5.8	≤20.3	≤30.5	5.7
441		602030H	≥320	≥3.7	≤6	≤20.3	≤31.0	6.0
442		652030P	≥300	≥3.7	≤6.3	≤19.1	≤31.0	5.6
443		702030H	≥360	≥3.7	≤7.0	≤20.5	≤30.8	6.7
444		782030	≥420	≥3.7	≤7.8	≤20.5	≤31.0	7.8
445		802030G	≥390	≥3.7	≤8.2	≤20.5	≤30.8	7.2
446		852030	≥450	≥3.7	≤8.5	≤20.0	≤31.0	8.3
447		902030	≥480	≥3.7	≤9.0	≤20.5	≤30.5	8.8
448		2033	322033	≥150	≥3.7	≤3.15	≤20.3	≤33.5
449	352033		≥180	≥3.7	≤3.5	≤20.5	≤33.5	3.6
450	502033G		≥270	≥3.7	≤5.0	≤20.5	≤33.5	5.2
451	602033		≥400	≥3.7	≤6	≤21.0	≤34.0	7.4
452	702033		≥400	≥3.7	≤6.9	≤19.8	≤33.5	7.4
453	102033H		≥610	≥3.7	≤10.2	≤20.5	≤33.5	11.1
454	2035	402035PG	≥220	≥3.7	≤4.2	≤20.5	≤35.5	4.3
455		402035	≥240	≥3.7	≤4.2	≤20.5	≤35.5	4.6
456		502035	≥280	≥3.7	≤5.3	≤20.5	≤35.5	5.3

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
457	2035	552035G	≥350	≥3.7	≤5.7	≤20.5	≤35.5	6.6
458		652035	≥400	≥3.7	≤6.5	≤20.5	≤35.5	7.4
459		672035	≥430	≥3.7	≤6.7	≤20.5	≤35.5	8.0
460		702035	≥450	≥3.7	≤6.8	≤20.5	≤35.5	8.3
461		802035H	≥500	≥3.7	≤8.0	≤20.5	≤35.5	9.2
462		832035	≥540	≥3.7	≤8.3	≤20.5	≤35.8	9.9
463		102035	≥650	≥3.7	≤10.0	≤20.5	≤35.8	11.8
464	2040	402040	≥280	≥3.7	≤4.0	≤21.0	≤40.5	5.4
465		442040	≥300	≥3.7	≤4.4	≤20.5	≤40.5	5.7
466		452040	≥320	≥3.7	≤4.7	≤20.5	≤40.5	6.1
467		502040H	≥400	≥3.7	≤5.0	≤20.0	≤42.0	7.5
468		552040	≥380	≥3.7	≤5.5	≤20.5	≤40.5	7.1
469		602040H	≥450	≥3.7	≤6.0	≤20.0	≤40.5	8.4
470		652040	≥450	≥3.7	≤6.5	≤20.5	≤40.5	8.4
471		702040H	≥500	≥3.7	≤7.0	≤20.5	≤40.5	9.2
472		752040	≥500	≥3.7	≤7.5	≤20.5	≤40.5	9.2
473		802040	≥580	≥3.7	≤8.0	≤20.5	≤40.5	10.6
474		852040G	≥650	≥3.7	≤8.5	≤20.5	≤40.5	11.9
475		902040	≥700	≥3.7	≤9.0	≤20.0	≤40.5	12.7
476		102040	≥850	≥3.7	≤10.3	≤20.5	≤40.5	15.4
477	2044	352044	≥280	≥3.7	≤3.45	≤20.3	≤44.5	5.4
478		472044HG	≥400	3.7	≤4.7	≤20.5	≤44.5	7.5
479		502044	≥420	≥3.7	≤5.0	≤20.5	≤44.5	7.9
480		552044	≥500	≥3.7	≤5.6	≤20.5	≤44.5	9.3
481		602044	≥550	≥3.7	≤6.2	≤20.5	≤44.5	10.1
482		652044	≥500	≥3.7	≤6.5	≤20.5	≤44.5	9.3
483		702044	≥600	≥3.7	≤7.0	≤20.5	≤44.5	11.0
484		852044G	≥720	≥3.7	≤8.5	≤20.5	≤44.5	13.1
485		942044	≥800	≥3.7	≤9.4	≤20.5	≤44.8	14.5
486	2048	452048	≥400	≥3.7	≤4.5	≤20.5	≤48.5	7.6
487		552048	≥550	≥3.7	≤5.5	≤20.5	≤48.5	10.2
488		602048	≥530	≥3.7	≤6.0	≤20.5	≤48.5	9.8
489		752048	≥670	≥3.7	≤7.5	≤20.5	≤49.0	12.3
490		852048P	≥720	≥3.7	≤8.5	≤20	≤48.5	13.1
491	2050	402050	≥360	≥3.7	≤4.1	≤20.0	≤49.5	6.9
492		602050G	≥500	≥3.7	≤5.8	≤20.0	≤50.5	9.3
493		882050H	≥1000	≥3.7	≤8.8	≤20.5	≤50.5	18.2
494	2055	852055	≥970	≥3.7	≤8.4	≤20.5	≤55.5	17.7

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.

Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
495	2055	102055	≥1150	≥3.7	≤10.0	≤20.5	≤55.5	20.8
496	2056	802056HV	≥1100	≥3.75	≤8.0	≤20.0	≤56.0	20.0
497	2058	882058P	≥1060	≥3.7	≤8.75	≤20.1	≤58.5	19.3
498		102058P	≥1000	≥3.7	≤10.5	≤20.5	≤58.5	18.2
499	2060	342060	≥400	≥3.7	≤3.4	≤20.5	≤60.5	7.7
500		402060M3	≥350	≥3.7	≤4.0	≤20.5	≤60.5	6.8
501		602060	≥770	≥3.7	≤6.0	≤20.0	≤60.5	14.1
502		702060H	≥900	≥3.7	≤7.29	≤20.5	≤60.5	16.4
503		752060	≥900	≥3.7	≤7.5	≤20.0	≤60.5	16.4
504		102060M3	≥1100	≥3.7	≤10.0	≤20.5	≤60.5	20.0
505	2065	352065	≥400	≥3.7	≤3.7	≤20.5	≤65.5	7.7
506		352065M3	≥350	≥3.7	≤3.5	≤20.5	≤65.5	6.9
507	2068	502068	≥650	≥3.7	≤5.2	≤20.5	≤68.5	12.1
508	2080	632080	≥1100	≥3.7	≤6.3	≤20.5	≤80.5	20.2
509		632080	≥950	≥3.7	≤6.1	≤20.5	≤80.5	17.5
510		702080HG	≥1200	≥3.7	≤7.0	≤20.5	≤82.0	21.9
511		762080	≥1100	≥3.7	≤7.2	≤20.5	≤80.5	20.2
512		802080M4	≥1100	≥3.7	≤8.0	≤20.5	≤80.5	20.2
513		102080G	≥1600	≥3.7	≤10.0	≤20.5	≤80.8	28.9
514	2083	302083P	≥420	≥3.7	≤3.0	≤20.5	≤83.5	8.3
515	2126	922126G	≥400	≥3.7	≤9.2	≤21.5	≤27.3	7.4
516	2143	402143	≥350	≥3.7	≤4.0	≤21.5	≤43.0	6.7
517		922143	≥800	≥3.7	≤9.2	≤21.5	≤43.5	14.5
518		102143	≥950	≥3.7	≤10.3	≤21.5	≤43.8	17.1
519	2148	492148	≥470	≥3.7	≤4.9	≤21.5	≤48.5	8.8
520	2222	302222	≥100	≥3.7	≤3.2	≤22.0	≤22.5	2.1
521		442223	≥220	≥3.7	≤4.4	≤22.5	≤23.5	4.2
522		452223G	≥210	≥3.7	≤4.5	≤22.5	≤23.5	4.0
523		622222	≥260	≥3.7	≤6.2	≤23.5	≤23	4.9
524	2227	402227	≥180	≥3.7	≤4.1	≤22.5	≤26.5	3.5
525	2238	752238	≥600	≥3.7	≤7.7	≤22.5	≤38.5	11.0
526	2238	372238	≥280	≥3.7	≤3.7	≤22.3	≤38.5	5.4
527		462238	≥350	≥3.7	≤4.65	≤22.5	≤38.5	6.6
528		502238	≥410	≥3.7	≤5.0	≤22.0	≤38.0	7.7
529		722238	≥600	≥3.7	≤7.2	≤22.5	≤38.8	11.0
530		952238	≥750	≥3.7	≤9.45	≤22.3	≤39.0	13.6
531		102238	≥800	≥3.7	≤10	≤22.5	≤39.0	14.5
532	2240	552240	≥450	≥3.7	≤5.5	≤22.5	≤40.5	8.4

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
533	2240	752240B	≥650	≥3.7	≤7.5	≤22.5	≤40.5	11.9
534	2245	582245	≥550	≥3.7	≤6.0	≤22.5	≤45.5	10.2
535		672245	≥700	≥3.7	≤6.7	≤22.3	≤45.5	12.8
536		682245	≥750	≥3.7	≤6.8	≤22.5	≤45	13.7
537		752245	≥760	≥3.7	≤7.5	≤23.0	≤45.5	13.9
538		782245P	≥720	≥3.7	≤7.75	≤22.3	≤45.5	13.2
539		2248	252248	≥200	≥3.7	≤2.7	≤22.5	≤48.8
540	302248		≥230	≥3.7	≤3.0	≤22.5	≤48.5	4.6
541	362248P		≥240	≥3.7	≤3.6	≤22.5	≤48.5	4.8
542	402248		≥450	≥3.7	≤4.0	≤22.5	≤48.5	8.5
543	502248H		≥500	≥3.7	≤5.0	≤22.5	≤48.0	9.3
544	602248H		≥680	≥3.7	≤6.0	≤22.5	≤48.5	12.5
545	752248		≥750	≥3.7	≤7.5	≤22.5	≤48.5	13.7
546	802248G		≥800	≥3.7	≤8.0	≤22.5	≤48.5	14.6
547	902248		≥900	≥3.7	≤8.9	≤22.3	≤48.8	16.3
548	2252		762252	≥850	≥3.7	≤7.6	≤22.0	≤52.0
549	2258	682258	≥950	≥3.7	≤6.9	≤22.5	≤58.7	17.3
550		702258	≥950	≥3.7	≤7.0	≤22.5	≤58.5	17.3
551		112258	≥1400	≥3.7	≤11.0	≤22.8	≤58.8	25.3
552	2260	482260	≥600	≥3.7	≤4.85	≤22.5	≤60.0	11.2
553		802260	≥1150	≥3.7	≤8.0	≤22.5	≤60.0	20.9
554		952260	≥1350	≥3.7	≤9.5	≤22.5	≤60.0	24.4
555	2294	502294	≥1000	≥3.7	≤5.0	≤22.5	≤95.0	18.6
556		802294	≥1650	≥3.7	≤7.3	≤22.5	≤95.0	30.0
557	2322	622222	≥260	≥3.7	≤6.2	≤23.5	≤23.0	4.9
558		702322	≥290	≥3.7	≤7.2	≤23.5	≤22.0	5.5
559	2323	302323	≥130	≥3.7	≤3.0	≤23.5	≤23.5	2.6
560		362323	≥165	≥3.7	≤3.8	≤23.5	≤23.5	3.3
561		402323H	≥180	≥3.7	≤4.3	≤23.5	≤24.0	3.5
562		502323	≥200	≥3.7	≤5.0	≤23.5	≤24.0	3.9
563		752323	≥340	≥3.7	≤7.5	≤23.5	≤24.5	6.3
564		902323	≥380	≥3.7	≤9	≤23.5	≤24.5	7.1
565		2325	502325	≥250	≥3.7	≤5.0	≤23.5	≤25.5
566	2327	332327	≥160	≥3.7	≤3.35	≤23.8	≤27.5	3.2
567	2328	352328H	≥200	≥3.7	≤3.5	≤23.3	≤28.0	3.9
568		422328	≥220	≥3.7	≤4.2	≤23	≤28.5	4.3
569	2329	502339B	≥420	≥3.7	≤5.2	≤23.5	≤39.5	7.9
570	2330	602330	≥450	≥3.7	≤6.0	≤23.5	≤30.5	8.3

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
571	2332	272332	≥165	≥3.7	≤2.7	≤23.5	≤32.5	3.3
572		402332	≥240	≥3.7	≤4.2	≤23.5	≤32.5	4.7
573		422332	≥240	≥3.7	≤4.0	≤22.9	≤32.0	4.6
574		442332	≥290	3.7	≤4.4	≤23.5	≤32.0	5.5
575		662332	≥420	≥3.7	≤6.6	≤23.5	≤32.5	7.8
576		952332	≥620	≥3.7	≤9.4	≤23.5	≤32.5	11.3
577	2335	252335	≥150	≥3.7	≤2.7	≤23.5	≤35.5	3.1
578		352335G	≥200	≥3.7	≤3.5	≤23.3	≤35.5	4.0
579		372335	≥270	≥3.7	≤3.65	≤23.2	≤35.5	5.2
580		502335	≥380	≥3.7	≤5.0	≤25.0	≤35.5	7.2
581		652335	≥450	≥3.7	≤6.5	≤23.5	≤35.5	8.4
582		752335	≥550	≥3.7	≤7.5	≤23.5	≤35.5	10.1
583		822335	≥760	≥3.7	≤8.2	≤25.5	≤35.5	13.8
584		852335	≥760	≥3.7	≤8.5	≤25.0	≤35.5	13.8
585	2338	482338	≥360	≥3.7	≤4.8	≤23.0	≤38.5	6.8
586		562338	≥450	≥3.7	≤5.7	≤23.5	≤38.5	8.4
587		602338	≥510	≥3.7	≤6.2	≤23.8	≤38.5	9.4
588		652338	≥500	≥3.7	≤6.8	≤23.5	≤38.5	9.3
589		702338M5	≥460	≥3.7	≤7.1	≤23.5	≤38.8	8.6
590	2339	302339	≥240	≥3.7	≤3.2	≤23.5	≤39.5	4.7
591		402339	≥360	≥3.7	≤4.0	≤23.5	≤39.5	6.8
592		422339	≥350	≥3.7	≤4.2	≤23.5	≤39.5	6.7
593		452339	≥350	≥3.7	≤4.5	≤23.5	≤39.5	6.7
594		502339	≥420	≥3.7	≤5.2	≤23.5	≤39.5	7.9
595		562339	≥460	≥3.7	≤5.6	≤23.5	≤39.5	8.6
596		602339	≥500	≥3.7	≤6.0	≤23.5	≤39.5	9.3
597		652339HG	≥580	≥3.7	≤6.4	≤23.5	≤39.5	10.7
598		702339	≥650	≥3.7	≤7.0	≤23.5	≤39.5	11.9
599		882339	≥750	≥3.7	≤8.8	≤23.5	≤39.8	13.6
600	2370	832370	≥1400	≥3.7	≤8.3	≤23.0	≤70.0	25.4
601	2372	542372G	≥1000	≥3.7	5.3	≤22.9	≤73.5	18.4
602	2424	402424HV	≥180	≥3.7	≤4.0	≤24.0	≤24.0	3.5
603	2425	302425	≥120	≥3.7	≤3	≤24.2	≤23.5	2.5
604		402425	≥170	≥3.7	≤4.0	≤24.2	≤23.5	3.3
605		602425	≥255	≥3.7	≤6.0	≤24.5	≤25.5	4.9
606		622425	≥320	≥3.7	≤6.1	≤24.5	≤26.7	6.0
607	2426	342426	≥180	≥3.7	≤3.5	≤24.0	≤26.0	3.5
608	2427	402427HV	≥250	≥3.8	≤4.0	≤24.0	≤27.0	4.8

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)	
609	2427	702427P	≥410	≥3.7	≤7.0	≤24.5	≤27.5	7.6	
610		782427P	≥410	≥3.7	≤7.8	≤24.5	≤27.0	7.6	
611	2438	402438	≥350	≥3.7	≤4.0	≤23.5	≤38.5	6.6	
612		602438	≥500	≥3.7	≤5.8	≤23.3	≤39.3	9.3	
613	2439	522439	≥500	≥3.7	≤5.2	≤24.5	≤38.5	9.3	
614		602439G	≥500	≥3.7	≤5.8	≤23.9	≤40.5	9.3	
615	2447	412447	≥450	≥3.7	≤4.1	≤24.5	≤47.5	8.5	
616	2448	562448	≥600	≥3.7	≤5.6	≤24	≤48.5	11.1	
617		652447	≥700	≥3.7	≤6.5	≤24	≤48.0	12.9	
618		702448	≥800	≥3.7	≤7.0	≤24.0	≤48.5	14.6	
619	2450	122450	≥60	≥3.7	≤1.2	≤24.5	≤50.0	1.7	
620	2487	252487	≥370	≥3.7	≤2.5	≤24.0	≤87.0	7.6	
621		692487	≥1650	≥3.7	≤6.85	≤24.3	≤87.5	29.9	
622	24122	1524122	≥180	≥3.7	≤1.35	≤23.8	≤120	4.7	
623	2525	252525	≥95	≥3.7	≤2.7	≤25.5	≤25.5	2.1	
624		302525	≥140	≥3.7	≤3.0	≤25.5	≤25.5	2.8	
625		402525	≥200	≥3.7	≤4.0	≤25.5	≤25.5	3.9	
626		422525	≥220	≥3.7	≤4.2	≤25.3	≤25.5	4.3	
627		452525	≥230	≥3.7	≤4.55	≤25.3	≤25.5	4.4	
628		462525	≥230	≥3.7	≤4.6	≤25.5	≤25.5	4.4	
629		502525	≥250	≥3.7	≤5.2	≤25.5	≤25.5	4.8	
630		582525	≥290	≥3.7	≤5.8	≤25.5	≤25.0	5.5	
631		602525	≥300	≥3.7	≤6.2	≤25.5	≤25.8	5.7	
632		802525	≥400	≥3.7	≤7.7	≤25.2	≤25.8	7.4	
633		102525	≥550	≥3.7	≤10.15	≤25.3	≤25.8	10.1	
634		2526	432526GHV	≥320	≥3.7	≤4.3	≤25.0	≤26.5	6.0
635			452526GHV	≥330	≥3.8	≤4.5	≤25.5	≤26.5	6.2
636	502526HV		≥370	≥3.8	≤5.0	≤25.0	≤26.5	6.9	
637	2530	252530	≥150	≥3.7	≤2.7	≤25.5	≤30.5	3.1	
638		302530G	≥120	≥3.7	≤3.0	≤25.5	≤30.5	2.6	
639		382530	≥260	≥3.7	≤3.8	≤25.5	≤30.5	5.0	
640		402530	≥250	≥3.7	≤4.2	≤25.5	≤30.5	4.8	
641		422530	≥285	≥3.7	≤4.2	≤24.8	≤30.0	5.4	
642		452530	≥280	≥3.7	≤4.5	≤25.5	≤30.5	5.4	
643		482530	≥300	≥3.7	≤5.0	≤25.5	≤30.5	5.7	
644		502530	≥370	≥3.7	≤5	≤25.5	≤30.5	6.9	
645		502530	≥390	≥3.7	≤5.15	≤27.0	≤30.3	7.3	
646		532530	≥350	≥3.7	≤5.3	≤26.0	≤30.5	6.6	



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)	
647	2530	602530	≥450	≥3.7	≤6.15	≤25.3	≤30.5	8.3	
648		652530H	≥460	≥3.7	≤6.5	≤25.5	≤30.8	8.5	
649		702530	≥500	≥3.7	≤7.2	≤25.3	≤30.5	9.2	
650	2532	332532	≥250	≥3.7	≤3.35	≤25.5	≤32.6	4.9	
651		952532	≥720	≥3.7	≤9.5	≤25.3	≤32.0	13.1	
652	2533	352533	≥245	≥3.7	≤3.6	≤25.5	≤33.5	4.8	
653		402533	≥240	≥3.7	≤4.2	≤25.5	≤33.5	4.7	
654		452533	≥350	≥3.7	≤4.7	≤25.5	≤33.5	6.6	
655		502533	≥370	≥3.7	≤5.2	≤25.5	≤33.5	7.0	
656		602533	≥450	≥3.7	≤6.0	≤25.5	≤33.5	8.4	
657		652533	≥500	≥3.7	≤6.7	≤25.0	≤33.5	9.2	
658		752533	≥550	≥3.7	≤7.5	≤25.5	≤33.5	10.1	
659		762533	≥600	≥3.7	≤7.6	≤25.5	≤33.5	11.0	
660		2535	402535	≥320	≥3.7	≤4.1	≤25.5	≤35.0	6.1
661			452535G	≥400	≥3.7	≤4.5	≤25.5	≤35.5	7.5
662	482535		≥370	≥3.7	≤4.8	≤25.5	≤35.5	7.0	
663	502535P		≥300	≥3.7	≤5.2	≤25.5	≤25.5	5.7	
664	502535		≥380	≥3.7	≤5	≤25.0	≤35.5	7.2	
665	502535G		≥400	≥3.7	≤5.1	≤25.5	≤35.5	7.5	
666	552535		≥430	≥3.7	≤5.4	≤25.5	≤34.5	8.0	
667	582535G		≥470	≥3.7	≤5.8	≤25.5	≤35.5	8.7	
668	592535		≥500	≥3.7	≤5.95	≤25.3	≤35.5	9.3	
669	602535		≥500	≥3.7	≤6.1	≤25.8	≤36.5	9.3	
670	702535		≥600	≥3.7	≤7.0	≤25.5	≤35.5	11.0	
671	842535		≥650	≥3.7	≤8.4	≤25.5	≤35.0	11.9	
672	952535		≥800	≥3.7	≤9.5	≤25.5	≤35.5	14.5	
673	982535		≥710	≥3.7	≤9.8	≤25.5	≤35.5	12.9	
674	2536	692536	≥620	≥3.7	≤6.9	≤25.5	≤37.0	11.4	
675		802536	≥740	≥3.7	≤7.95	≤25.0	≤37.0	13.5	
676		882536	≥700	≥3.7	≤8.8	≤25.5	≤37.5	12.8	
677		902536	≥750	≥3.7	≤9.3	≤25.5	≤37	13.7	
678	2539	452539	≥420	≥3.7	≤4.5	≤25.3	≤39.5	7.9	
679		452539B	≥420	≥3.7	≤4.15	≤25.3	≤39.5	7.9	
680	2540	582540	≥560	≥3.7	≤5.8	≤25.5	≤40.8	10.4	
681		602540	≥580	≥3.7	≤6.0	≤25.5	≤40.5	10.7	
682		652540	≥650	≥3.7	≤6.5	≤25.5	≤41.0	11.9	
683		852540	≥800	≥3.7	≤8.5	≤25.5	≤40.5	14.6	
684		902540P	≥700	≥3.7	≤9.0	≤25.5	≤41.0	12.8	

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
685	2540	102540	≥1000	≥3.7	≤10	≤25.5	≤41.0	18.2
686	2546	382546	≥400	≥3.7	≤3.8	≤25.8	≤45.8	7.6
687	2550	532550P	≥520	≥3.7	≤5.3	≤24.5	≤50.0	9.8
688		702550	≥800	≥3.7	≤7.5	≤25.0	≤50.0	14.6
689		802550	≥950	≥3.7	≤8.0	≤25.5	≤50.5	17.3
690		852550	≥1000	≥3.7	≤8.5	≤25.5	≤50.5	18.3
691		902550	≥1100	≥3.7	≤9.0	≤25.5	≤50.5	20.0
692		932550	≥1200	≥3.7	≤9.3	≤25.5	≤50.5	21.8
693		102550	≥1300	≥3.7	≤10.0	≤25.5	≤50.5	23.6
694		2553	802553	≥1000	≥3.7	≤8	≤25.5	≤53.5
695	2570	632570	≥1250	≥3.7	≤6.3	≤25.8	≤70.5	22.8
696		102570	≥1900	≥3.7	≤10.0	≤25.5	≤70.5	34.2
697	2573	762573	≥1500	≥3.7	≤7.6	≤25.5	≤74.0	27.2
698		102573	≥2000	≥3.7	≤10.0	≤25.5	≤73.8	36.0
699	2725	342625	≥180	≥3.7	≤3.4	≤26.5	≤24.5	3.6
700	2626	452626	≥230	≥3.7	≤4.4	≤26.5	≤26.0	4.4
701	2628	402628	≥240	≥3.7	≤4.0	≤26.5	≤28.5	4.6
702		502628	≥330	≥3.7	≤5.0	≤26.5	≤28.5	6.2
703		512628	≥300	≥3.7	≤5.15	≤26.0	≤28.5	5.7
704	2629	342629	≥220	≥3.7	≤3.4	≤26.5	≤29.0	4.3
705		372629	≥220	≥3.7	≤3.6	≤26.0	≤29.0	4.3
706	2634	232634	≥150	≥3.7	≤2.3	≤28.5	≤34.5	3.2
707		342634	≥270	≥3.7	≤3.4	≤25.7	≤34.5	5.2
708		452634	≥380	≥3.7	≤4.7	≤25.6	≤34.0	7.2
709		452634PG	≥310	≥3.7	≤4.7	≤26.5	≤34.5	5.9
710		632634	≥500	≥3.7	≤6.3	≤26.5	≤34.0	9.3
711		702634G	≥610	≥3.7	≤7.0	≤26.5	≤34.5	11.2
712	2637	502637	≥480	≥3.7	≤5.0	≤26.5	≤37.5	8.9
713		652637	≥650	≥3.7	≤6.5	≤26.5	≤38.0	11.9
714		762638	≥730	≥3.7	≤7.6	≤26.5	≤38.0	13.3
715	2638	582638	≥580	≥3.7	≤5.8	≤26.5	≤38.5	10.7
716		602638	≥600	≥3.7	≤6.0	≤26.5	≤38.0	11.1
717	2652	502652	≥670	≥3.7	≤5.0	≤26.5	≤52.5	12.4
718		602652	≥800	≥3.7	≤6.2	≤26.5	≤52.5	14.7
719	2655	402655	≥540	≥3.7	≤4	≤26.0	≤55.0	10.2
720	2663	602663	≥1000	≥3.7	≤6.2	≤26.3	≤63.5	18.4
721	2682	652682G	≥1500	≥3.7	≤6.4	≤25.9	≤82.0	27.3
722	2725	562725	≥320	≥3.7	≤5.6	≤26.8	≤25.5	6.0

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
723	2728	472728HV	≥350	≥3.7	≤4.7	≤27.5	≤28.5	6.6
724		502728	≥400	≥3.7	≤5.05	≤27.5	≤28.5	7.5
725	2730	382730	≥270	≥3.7	≤3.8	≤27.5	≤30.0	5.2
726		402730	≥300	≥3.7	≤4.0	≤27.3	≤30.5	5.7
727		502730	≥360	≥3.7	≤5.0	≤27.5	≤30.8	6.8
728		552730	≥400	≥3.7	≤5.5	≤27.8	≤30.5	7.5
729		602730	≥400	≥3.7	≤6.0	≤27.5	≤31.0	7.5
730		902730G	≥730	≥3.7	≤9.1	≤27.5	≤30.8	13.3
731	2734	852734	≥750	≥3.7	≤8.5	≤27.5	≤34.5	13.7
732	2738	382738	≥350	≥3.7	≤3.8	≤27.5	≤38.5	6.7
733		432738	≥410	≥3.7	≤4.3	≤27.3	≤38.5	7.7
734	2739	402739	≥400	≥3.7	≤4.0	≤26.8	≤38.5	7.6
735	2742	402742	≥400	≥3.7	≤3.9	≤27.5	≤42.5	7.6
736		482745	≥500	≥3.7	≤4.8	≤27.0	≤43.5	9.4
737		752742	≥800	≥3.7	≤7.5	≤27.5	≤42.5	14.6
738		922742	≥1100	≥3.7	≤9.3	≤27.5	≤43.0	20.0
739		932742	≥1000	≥3.7	≤9.3	≤27.5	≤42.5	18.3
740	2745	382745	≥450	≥3.7	≤3.75	≤26.8	≤45.5	8.5
741		402745	≥480	≥3.7	≤4.0	≤27.5	≤45.5	9.1
742		502745	≥600	≥3.7	≤5.00	≤27.0	≤45.5	11.1
743		642745	≥800	≥3.7	≤6.4	≤27	≤45.8	14.6
744		902745	≥1100	≥3.7	≤9.0	≤27.0	≤46.0	20.0
745	2775	372775	≥750	≥3.7	≤3.7	≤27.17	≤76.0	13.6
746	2827	402827	≥250	≥3.7	≤3.85	≤28.3	≤27.0	4.8
747		772827	≥500	≥3.7	≤7.7	≤28.0	≤28.0	9.2
748	2832	432832	≥380	≥3.7	≤4.3	≤28.5	≤32.5	7.2
749	2834	342834	≥310	≥3.7	≤3.4	≤28.5	≤35.5	6.0
750		502834	≥420	≥3.7	≤5.0	≤28.5	≤34.5	7.9
751		502834HV	≥570	≥3.7	≤5.0	≤28.5	≤34.5	10.5
752		682834	≥600	≥3.7	≤7.0	≤28.3	≤34.8	11.0
753		702834	≥640	≥3.7	≤7.05	≤28.5	≤35.0	11.8
754	2839	482839G	≥560	≥3.7	≤5.0	≤28.5	≤40.0	10.4
755	2844	252844	≥250	≥3.7	≤2.7	≤28.3	≤44.0	5.0
756		402844	≥510	≥3.7	≤4.0	≤28.5	≤44.0	9.6
757		802844	≥1000	≥3.7	≤8.0	≤28.5	≤45.0	18.3
758	2846	612846	≥750	≥3.7	≤6.1	≤28.0	≤46.5	13.8
759		922846	≥1100	≥3.7	≤9.2	≤27.5	≤46.2	20.0
760	2880	402880	≥850	≥3.7	≤4.0	≤29.0	≤80.5	16.0

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
761	2880	432880	≥1000	≥3.7	≤4.3	≤29.0	≤80.5	18.7
762	2897	752897G	≥2250	≥3.7	≤7.5	≤28.5	≤97.5	40.7
763	2933	402933	≥370	≥3.7	≤4.0	≤29.0	≤33.5	7.0
764	2934	852934	≥800	≥3.7	≤8.5	≤29.0	≤34.5	14.6
765		902934	≥850	≥3.7	≤9.0	≤29.0	≤34.5	15.4
766	2946	342946G	≥450	≥3.7	≤3.45	≤28	≤46.0	8.5
767	2950	652950	≥900	≥3.7	≤6.5	≤29.5	≤50.0	16.5
768	2952	452952	≥770	≥3.7	≤4.5	≤29.5	≤52.5	14.2
769		672952	≥1100	≥3.7	≤6.7	≤29.0	≤52.0	20.1
770	2953	282953P	≥300	≥3.7	≤2.8	≤29.5	≤53.5	6.1
771	29127	3829127	≥1650	≥3.7	≤3.9	≤29.5	≤127.5	30.0
772		6029127	≥2500	≥3.7	≤6.2	≤29.5	≤127.5	45.2
773	3023	263023P	≥80	≥3.7	≤2.40	≤29.5	≤23.0	1.8
774	3030	353030	≥250	≥3.7	≤3.5	≤30.5	≤30.5	4.9
775		353030HV	≥290	≥3.75	≤3.5	≤30.5	≤30.5	5.6
776		453030	≥360	≥3.7	≤4.4	≤30.5	≤30.5	6.8
777		463030	≥400	≥3.7	≤4.6	≤30.5	≤30.5	7.5
778		503030	≥400	≥3.7	≤5.0	≤30.5	≤30.5	7.5
779		563030	≥480	≥3.7	≤5.8	≤30.5	≤30.8	8.9
780		603030	≥520	≥3.7	≤6.0	≤30.0	≤30.8	9.6
781		683030	≥590	≥3.7	≤6.8	≤30.5	≤30.5	10.9
782		703030	≥600	≥3.7	≤7.0	≤30.5	≤30.5	11.0
783		3032	303032	≥260	≥3.7	≤3.0	≤30.3	≤32.5
784	3035	303035	≥280	≥3.7	≤3.2	≤30.5	≤35.5	5.5
785		383035	≥300	≥3.7	≤3.8	≤30.5	≤35.5	5.8
786		403035P	≥280	≥3.7	≤4.0	≤30.5	≤35.5	5.5
787		403035	≥380	≥3.7	≤4.0	≤30.5	≤35.5	7.2
788		483035	≥520	≥3.7	≤4.8	≤30.0	≤35.0	9.7
789		503035	≥500	≥3.7	≤5.2	≤30.5	≤35.8	9.3
790		503035G	≥450	≥3.7	≤5.0	≤30.5	≤35.8	8.5
791		603035	≥600	≥3.7	≤6.2	≤30.5	≤35.8	11.1
792		603636HV	≥800	≥3.7	≤6.15	≤30.0	≤36.0	13.4
793		803035	≥800	≥3.7	≤7.8	≤30.3	≤35.8	14.6
794	3036	803036G	≥800	≥3.7	≤8.0	≤30.5	≤36.0	14.6
795		803036HG	≥800	≥3.7	≤8	≤30.5	≤36.0	14.6
796	3038	423038G	≥450	≥3.7	≤4.2	≤30.5	≤38.7	8.5
797		453038P	≥460	≥3.7	≤4.5	≤30.5	≤38.7	8.7
798		453038	≥530	≥3.7	≤4.5	≤30.3	≤38.5	9.9

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
799	3038	463038	≥500	≥3.7	≤4.6	≤30.5	≤38.5	9.4
800	3040	203040	≥210	≥3.7	≤2.5	≤36.0	≤40.5	4.4
801		303040PG	≥255	≥3.7	≤3.1	≤30.5	≤40.5	5.1
802		303040	≥330	≥3.7	≤3.2	≤30.5	≤40.5	6.4
803		303040G	≥310	≥3.7	≤3.1	≤30.5	≤40.5	6.1
804		353040	≥350	≥3.7	≤3.5	≤30.5	≤40.5	6.8
805		363040	≥350	≥3.7	≤3.6	≤30.5	≤40.5	6.8
806		383040	≥400	≥3.7	≤3.8	≤30.5	≤40.5	7.6
807		403040	≥420	≥3.7	≤4.0	≤30.5	≤40.5	8.0
808		423040G	≥450	≥3.7	≤4.4	≤30.5	≤40.5	8.5
809		503040B	≥600	≥3.7	≤5.0	≤30.5	≤40.5	11.1
810		503040H	≥560	≥3.7	≤5.0	≤30.5	≤40.5	10.4
811		553040G	≥680	≥3.7	≤5.5	≤30.2	≤42	12.5
812		503040	≥520	≥3.7	≤5.0	≤30.5	≤40.5	9.7
813		523040	≥600	≥3.7	≤5.2	≤30.3	≤41.0	11.1
814		553040	≥630	≥3.7	≤5.7	≤30.5	≤40.5	11.7
815		603040G	≥650	≥3.7	≤6.0	≤30.5	≤40.5	12.0
816		653040	≥750	≥3.7	≤6.5	≤30.5	≤40.5	13.8
817		683040HG	≥800	≥3.7	≤6.8	≤30.5	≤40.5	14.6
818		803040G	≥950	≥3.7	≤8.0	≤30.5	≤40.8	17.3
819		853040	≥1000	≥3.7	≤8.5	≤30.5	≤40.8	18.3
820	903040	≥1000	≥3.7	≤9.0	≤30.5	≤40.8	18.3	
821	3045	293045	≥360	≥3.7	≤2.95	≤31.0	≤46.0	7.0
822		473045	≥700	≥3.7	≤4.7	≤30.5	≤45.5	12.9
823		603045	≥850	≥3.7	≤6.2	≤30.5	≤45.8	15.6
824		603045P	≥700	≥3.7	≤6.1	≤30.5	≤45.8	13.0
825		743045	≥1020	≥3.7	≤7.4	≤30.5	≤45.8	18.7
826		763045	≥1080	≥3.7	≤7.6	≤30.5	≤45.8	19.7
827		803045	≥1150	≥3.7	≤8.0	≤30.5	≤45.8	21.0
828		943045	≥1350	≥3.7	≤9.4	≤30.5	≤46.0	24.5
829		103045	≥1400	≥3.7	≤10.2	≤30.3	≤45.8	25.4
830	3048	123048	≥80	≥3.7	≤1.2	≤30.0	≤48.0	2.1
831		133048	≥85	≥3.7	≤1.3	≤30.0	≤48.0	2.2
832		323048G	≥480	≥3.7	≤3.3	≤30.5	≤50.0	9.2
833		353048	≥500	≥3.7	≤3.7	≤30.5	≤48.5	9.5
834		403048	≥580	≥3.7	≤4.0	≤30.5	≤48.5	10.9
835		453048P	≥450	≥3.7	≤4.5	≤30.5	≤48.5	8.6
836		453048	≥600	≥3.7	≤4.5	≤30.5	≤48.5	11.2

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
837	3048	453048H	≥650	≥3.7	≤4.7	≤30.5	≤48.5	12.1
838		483048	≥700	≥3.7	≤5.0	≤30.5	≤48.5	13.0
839		503048H	≥750	≥3.7	≤5.1	≤30.0	≤48.0	13.8
840		503048L	≥730	≥3.7	≤5.0	≤30.3	≤48.0	13.5
841		553048	≥800	≥3.7	≤5.5	≤30.0	≤48.0	14.7
842		603048H	≥870	≥3.7	≤6	≤30.0	≤48.5	15.9
843		603048B	≥900	≥3.7	≤6	≤30.5	≤48.5	16.5
844		603048	≥850	≥3.7	≤6.3	≤30.5	≤48.5	15.6
845		603048P	≥800	≥3.7	≤7	≤30.5	≤48.5	14.7
846		703048G	≥1000	≥3.7	≤7.0	≤29.5	≤50.0	18.4
847		703048	≥1020	≥3.7	≤7.0	≤30.5	≤48.5	18.7
848		743048	≥1100	≥3.7	≤7.4	≤30.5	≤48.8	20.1
849		743048G	≥1100	≥3.7	≤7.4	≤30.5	≤48.5	20.1
850		753048M3	≥1000	≥3.7	≤7.5	≤30.5	≤50.0	18.4
851		753048	≥1100	≥3.7	≤7.4	≤29.5	≤48.8	20.1
852		803048	≥950	≥3.7	≤8.0	≤30.5	≤48.5	17.3
853		853048	≥1200	≥3.7	≤8.45	≤30.3	≤48.5	21.9
854		953048	≥1400	≥3.7	≤9.5	≤30.5	≤48.5	25.4
855		953048P	≥1250	≥3.7	≤9.5	≤30.5	≤48.5	22.8
856		103048	≥1500	≥3.7	≤10.0	≤30.5	≤48.8	27.2
857	3050	453050G	≥700	≥3.7	≤4.5	≤30.0	≤51.5	13.0
858		553050	≥820	≥3.7	≤5.5	≤30.5	≤49.5	15.1
859	3060	503060	≥900	≥3.7	≤5.0	≤30.5	≤60.5	16.6
860		603060M2	≥1000	≥3.7	≤6.0	≤30.5	≤60.5	18.5
861		643060P	≥850	≥3.7	≤6.4	≤30.5	≤60.5	15.8
862		643060P	≥900	≥3.7	≤6.4	≤30.5	≤60.5	16.6
863		703060	≥1400	≥3.7	≤7.0	≤30.5	≤60.5	25.5
864		903060	≥1750	≥3.7	≤9.2	≤30.5	≤60.5	31.6
865		103060HV	≥2100	≥3.8	≤9.15	≤29.8	≤59.5	37.7
866	3066	693066	≥1500	≥3.7	≤6.9	≤30.5	≤66.5	27.3
867		893066	≥2000	≥3.7	≤8.9	≤30.5	≤66.8	36.0
868	3080	753080	≥2000	≥3.7	≤7.5	≤30.5	≤80.5	36.2
869	30134	7530134	≥3500	≥3.7	≤7.5	≤30.0	≤135.0	62.6
870		8530134	≥3800	≥3.7	≤8.5	≤30.5	≤134.5	68.0
871	30158	4030158	≥2100	≥3.7	≤4.1	≤30.5	≤158.0	37.7
872	30160	8030160M2	≥4100	≥3.7	≤7.8	≤30.0	≤160.5	72.8
873	3128	263128	≥180	≥3.7	≤2.8	≤31.5	≤28.5	3.6
874		513128	≥410	≥3.7	≤5.1	≤31.8	≤28.5	7.7

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



2019 Lithium Polymer Cell Selection Guide

509 East Ellis Road, Norton Shores, MI 49441 U.S.A.

Toll Free No. 1-800-798-7740

ISO 13485

Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
875	3135	503135	≥500	≥3.7	≤5.0	≤31.5	≤35.5	9.3
876		553135	≥560	≥3.7	≤5.5	≤31.5	≤36.0	10.4
877	3140	963140P	≥1000	≥3.7	≤9.6	≤31.5	≤40.5	18.3
878	3144	473144	≥700	≥3.7	≤4.7	≤31.5	≤45.0	13.0
879	3147	333147	≥500	≥3.7	≤3.3	≤31.0	≤47.5	9.5
880	3157	553157P	≥950	≥3.7	≤5.5	≤31	≤57.5	17.5
881		583157G	≥1100	≥3.7	≤6.0	≤31.5	≤57.5	20.2
882	3233	103233	≥1020	≥3.7	≤9.8	≤32.5	≤34.2	18.7
883		103233N	≥950	≥3.7	≤9.8	≤32.5	≤34.0	17.2
884	3240	563240	≥750	≥3.7	≤5.6	≤32.5	≤40.5	13.8
885	3247	613247	≥1000	≥3.7	≤6.1	≤32.0	≤47.8	18.4
886	3248	283248	≥430	≥3.7	≤2.8	≤32.5	≤48.5	8.3
887		453248G	≥800	≥3.7	≤4.6	≤32.3	≤49.5	14.8
888		553248	≥900	≥3.7	≤5.5	≤32.0	≤48.0	16.5
889		553248H	≥1000	≥3.7	≤5.5	≤32.5	≤48.0	18.4
890		103250	≥1850	≥3.7	≤10	≤32.8	≤50.5	29.9
891	3254	403254	≥780	≥3.7	≤4.0	≤32.0	≤54.0	14.5
892	3270	253270P	≥475	≥3.7	≤2.5	≤32	≤70.5	9.4
893		603270	≥1500	≥3.7	≤6.0	≤32.0	≤70.5	27.4
894		663270	≥1500	≥3.7	≤6.6	≤32.5	≤70.5	27.4
895		803270	≥2000	≥3.7	≤8.3	≤32.0	≤70.5	36.1
896		813270	≥2000	≥3.7	≤8.1	≤32.0	≤70.5	36.1
897	3285	343285	≥950	≥3.7	≤3.4	≤32.0	≤84.5	17.9
898	3328	943328	≥810	≥3.7	≤9.5	≤33.5	≤28.5	14.7
899	3339	423339	≥570	≥3.7	≤4.2	≤33.0	≤39.5	10.6
900		573440	≥800	≥3.7	≤5.7	≤34.5	≤40.4	14.7
901		903542G	≥1500	≥3.7	≤9.0	≤34.8	≤40.5	27.2
902	3340	443340	≥620	≥3.7	≤4.4	≤33.5	≤40.0	11.5
903	3341	473341	≥720	≥3.7	≤4.3	≤33.3	≤41.5	13.3
904	3342	573342	≥820	≥3.7	≤5.7	≤33.5	≤42.5	15.1
905		703342	≥1000	≥3.7	≤7.0	≤33.3	≤43.0	18.4
906	3343	863343	≥1400	≥3.7	≤8.8	≤33.5	≤43.5	25.4
907	3434	283434	≥260	≥3.7	≤2.8	≤34.5	≤34.5	5.2
908		683434	≥780	≥3.7	≤6.8	≤34.0	≤34.8	14.3
909		103434H	≥1150	≥3.7	≤10.0	≤34.5	≤34.5	21.0
910		103434	≥1050	≥3.7	≤10.0	≤34.5	≤34.8	19.2
911		113434	≥1250	≥3.7	≤11	≤34.5	≤35.0	22.8
912	3436	323436G	≥330	≥3.7	≤3.2	≤34.3	≤35.0	6.4

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
913	3436	383436	≥400	≥3.7	≤3.8	≤34.5	≤36.5	7.6
914		503436	≥550	≥3.7	≤5.0	≤34.5	≤36.5	10.3
915		553436	≥620	≥3.7	≤5.7	≤34.5	≤36.5	11.5
916		553436H	≥650	≥3.7	≤5.5	≤34.5	≤36.0	12.0
917	3438	303439G	≥350	≥3.7	≤2.95	≤33.5	≤38.5	6.8
918		403438	≥470	≥3.7	≤3.9	≤34.0	≤38.5	8.9
919		803438	≥1100	≥3.7	≤8	≤34.0	≤38.0	20.1
920	3439	303439G	≥350	≥3.7	≤2.97	≤34.0	≤39.5	6.8
921		303439	≥350	≥3.7	2.95	≤33.5	≤38.5	6.8
922	3440	283440	≥340	≥3.7	2.85	≤33.8	≤39.5	6.6
923		753440P	≥950	≥3.7	≤7.5	≤33.5	≤40.5	17.3
924		803440	≥1100	≥3.7	≤8.0	≤34.5	≤40.5	20.1
925	3441	253441	≥380	≥3.7	≤2.6	≤34.5	≤40.5	7.4
926		713441G	≥1100	≥3.7	≤7.2	≤34.0	≤42.0	20.1
927		103441	≥1450	≥3.7	≤9.9	≤34.0	≤41.0	26.3
928		113441	≥1600	≥3.7	≤11.3	≤34.0	≤41.5	29.0
929	3442	373442	≥500	≥3.7	≤3.7	≤34.5	≤42.5	9.5
930		373442G	≥480	≥3.7	≤3.7	≤36.5	≤42.5	9.2
931		403442	≥560	≥3.7	≤4.2	≤34.5	≤42.5	10.5
932		443442	≥640	≥3.7	≤4.4	≤34.5	≤42.5	11.9
933		453442G	≥650	≥3.7	≤4.7	≤34.5	≤42.5	12.1
934		503442	≥750	≥3.7	≤5.2	≤34.5	≤42.5	13.8
935		553442	≥800	≥3.7	≤5.3	≤34.5	≤42.5	14.7
936		653442	≥900	≥3.7	≤6.5	≤34.5	≤42.5	16.5
937		693442	≥1000	≥3.7	≤6.9	≤34.6	≤43.0	18.4
938		703442	≥1100	≥3.7	≤7.2	≤34.5	≤42.5	20.1
939		743442G	≥1100	≥3.7	≤7.4	≤34.5	≤42.8	20.1
940		933442G	≥1450	≥3.7	≤9.3	≤34.0	≤42.5	26.3
941	3444	363444	≥500	≥3.7	≤3.6	≤34.5	≤44.5	9.5
942		393444	≥500	≥3.7	≤3.9	≤34.5	≤44.5	9.5
943		603444M3	≥850	≥3.7	≤6.3	≤34.5	≤44.5	15.6
944		703444M3	≥1000	≥3.7	≤7.2	≤33.5	≤44.5	18.4
945		863444	≥1400	≥3.7	≤8.6	≤34.0	≤44.5	25.4
946	3445	233445	≥300	≥3.7	≤2.5	≤34.5	≤45.5	6.0
947		353445	≥470	≥3.7	≤3.4	≤34.5	≤44.8	9.0
948		383445	≥550	≥3.7	≤3.8	≤34.5	≤45.5	10.4
949		453445	≥700	≥3.7	≤4.5	≤34.5	≤45.5	13.8
950		503445G	≥750	≥3.7	≤5.3	≤33.7	≤45.0	13.9

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
951	3445	563445	≥820	≥3.7	≤5.6	≤34.5	≤45.5	15.1
952		603445G	≥1000	≥3.7	≤6.2	≤34.5	≤45.5	18.4
953		753445	≥1350	≥3.7	≤7.5	≤35.5	≤46	13.8
954		903445	≥1450	≥3.7	≤9.0	≤34.5	≤45.8	26.3
955		903445G	≥1450	≥3.7	≤9.0	≤34.5	≤45.3	26.3
956		103445	≥1500	≥3.7	≤10.2	≤34.5	≤45.5	27.2
957		113445	≥2000	≥3.7	≤11.5	≤34.5	≤45.8	36.0
958	3447	603447	≥950	≥3.7	≤6.0	≤34.0	≤47.5	17.4
959		793447G	≥1400	≥3.7	≤7.9	≤34.0	≤47.5	25.4
960	3448	303448	≥500	≥3.7	≤3.2	≤34.5	≤48.5	9.6
961		333448	≥500	≥3.7	≤3.3	≤34.5	≤48.5	9.6
962		403448	≥700	≥3.7	≤4.0	≤34.5	≤48.5	13.1
963		453448	≥780	≥3.7	≤4.5	≤34.3	≤49.5	14.5
964		523448	≥800	≥3.7	≤5.2	≤34.5	≤48.5	14.8
965		603448	≥1000	≥3.7	≤6.0	≤34.5	≤48.0	18.4
966		623448P	≥1000	≥3.7	≤6.2	≤34.5	≤48.5	18.4
967		703448H	≥1200	≥3.7	≤6.95	≤34.3	≤48.5	21.9
968		713448	≥1300	≥3.7	≤7.0	≤34.0	≤49.0	23.7
969		733448	≥1250	≥3.7	≤7.3	≤34.5	≤48.5	22.8
970		833448	≥1500	≥3.7	≤8.3	≤34.5	≤48.5	27.2
971		853448	≥1500	≥3.7	≤8.5	≤34.5	≤48.5	27.2
972		983448m3	≥1400	≥3.7	≤9.8	≤34.5	≤48.8	25.5
973		103448M3	≥1500	≥3.7	≤10.2	≤34.5	≤48.8	27.2
974		103448	≥1700	≥3.7	≤10.0	≤34.5	≤48.8	30.7
975	3450	263450P	≥300	≥3.7	≤2.6	≤34.0	≤50.0	6.1
976		273450	≥400	≥3.7	≤2.7	≤34.5	≤50.5	7.9
977		303450H	≥510	≥3.7	≤3.2	≤34.5	≤50.5	9.8
978		383450	≥650	≥3.7	≤3.8	≤34.5	≤50.5	12.2
979		433550	≥800	≥3.7	≤4.3	≤35.5	≤50.5	14.8
980		453450	≥820	≥3.7	≤4.6	≤34.5	≤50.5	15.2
981		473450	≥850	≥3.7	≤4.7	≤34.5	≤50.5	15.7
982		503450H	≥900	≥3.7	≤5.2	≤34.5	≤50.5	16.6
983		553450P	≥850	≥3.7	≤5.6	≤34.5	≤50.5	15.7
984		553450	≥1000	≥3.7	≤5.4	≤34.4	≤50.0	18.4
985		583450G	≥1000	≥3.7	≤5.8	≤34.5	≤50.5	18.4
986		583450H	≥1050	≥3.7	≤5.9	≤34.5	≤50.5	19.3
987		603450M2	≥1000	≥3.7	≤6.2	≤34.5	≤50.5	18.4
988		653450	≥1250	≥3.7	≤6.7	≤34.5	≤50.5	22.8

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
989	3450	653450P	≥1000	≥3.7	≤6.5	≤34.5	≤50.5	18.4
990		653450	≥1200	≥3.7	≤6.7	≤34.5	≤50.5	22.0
991		673450	≥1400	≥3.7	≤7.3	≤34.5	≤50.3	25.5
992		703450	≥1300	≥3.7	≤7	≤34.5	≤50.5	23.7
993		733450G	≥1380	≥3.7	≤7.3	≤34.0	≤50.5	25.1
994		753450	≥1400	≥3.7	≤7.5	≤34.5	≤50.5	25.5
995		763450	≥1200	≥3.7	≤7.5	≤34.5	≤50.5	22.0
996		803450D	≥1500	≥3.7	≤8.3	≤35.2	≤50	27.2
997		883450	≥1500	≥3.7	≤8.8	≤34.5	≤50.5	27.2
998		103450G	≥1750	≥3.7	≤10.0	≤34.5	≤50.5	31.6
999		103450	≥1900	≥3.7	≤10.0	≤34.5	≤51.0	34.3
1000		103450	≥1800	≥3.7	≤10.0	≤34.5	≤50.5	32.5
1001		103450B	≥2000	≥3.7	≤10.3	≤34.5	≤50.5	36.0
1002		3451	543451	≥950	≥3.7	≤5.4	≤34.5	≤51.0
1003	3458	383458	≥760	≥3.7	≤3.8	≤34.5	≤58.5	14.2
1004		523458	≥1100	≥3.7	≤5.2	≤34.5	≤58.5	20.3
1005		823458N	≥1700	≥3.7	≤8.4	≤35.0	≤58.5	30.8
1006		843458	≥1700	≥3.7	≤8.4	≤34.0	≤58.8	30.8
1007	3460	483460	≥1050	≥3.7	≤4.8	≤34.5	≤60.8	19.4
1008		503460	≥1080	≥3.7	≤4.8	≤34	≤60.0	19.9
1009	3465	423465	≥1000	≥3.7	≤4.2	≤34.5	≤65.5	18.6
1010		653465G	≥1650	≥3.7	≤6.5	≤34.0	≤65.0	30.0
1011		703465	≥1700	≥3.7	≤7.0	≤34.5	≤65.5	30.9
1012		803465G	≥2000	≥3.7	≤8.2	≤34.5	≤65.5	36.1
1013		853465M3	≥1900	≥3.7	≤8.5	≤34.5	≤65.5	34.4
1014		113465	≥3000	≥3.7	≤11	≤34.5	≤65	53.6
1015	3482	503482	≥1550	≥3.7	≤5.0	≤34.0	≤82.0	28.4
1016	3496	603496	≥2100	≥3.7	≤6.0	≤33.9	≤96.5	38.2
1017		643496	≥2200	≥3.7	≤6.4	≤34.5	≤96.8	40.0
1018		103496	≥3800	≥3.7	≤10.0	≤34.5	≤96.8	67.9
1019	3535	833535	≥950	≥3.7	≤8.3	≤35.0	≤35.0	17.3
1020		103535	≥1300	≥3.7	≤10.4	≤35.0	≤35.0	23.7
1021	3441	253541	≥380	≥3.7	≤2.6	≤34.5	≤40.5	7.4
1022	3545	383545G	≥550	≥3.7	≤3.9	≤35.8	≤46	10.4
1023	3550	253550	≥320	≥3.7	≤2.40	≤35.3	≤51.0	6.5
1024	3560	523560	≥1150	≥3.7	≤5.2	≤35.5	≤60.5	21.2
1025		553560	≥1260	≥3.7	≤5.5	≤35.5	≤62.5	23.2
1026		843560M3	≥1700	≥3.7	≤8.4	≤35.5	≤60.5	30.9

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
1027	3562	353562	≥830	≥3.7	≤3.5	≤35.3	≤62.0	15.5
1028		423562P	≥950	≥3.7	≤4.25	≤35.5	≤62.5	17.6
1029		503562	≥1250	≥3.7	≤5.0	≤35.5	≤62.5	23.0
1030		503562M3	≥1100	≥3.7	≤5.2	≤35.0	≤62.5	20.4
1031		593562	≥1400	≥3.7	≤5.9	≤35.3	≤62.8	25.6
1032		803562	≥2000	≥3.7	≤8.0	≤35.3	≤63.0	36.1
1033	3566	683566	≥1750	≥3.7	≤6.75	≤35.0	≤66.0	31.8
1034	3568	363568	≥840	≥3.7	≤3.6	≤35.5	≤66.8	15.8
1035		543568	≥1450	≥3.7	≤5.7	≤35.0	≤66.8	26.5
1036	3640	553640	≥850	≥3.7	≤5.45	≤36.0	≤40.0	15.6
1037		553640HV	≥900	≥3.7	≤5.45	≤36.0	≤40.0	16.5
1038		653640G	≥1000	≥3.7	≤6.45	≤36.3	≤40.5	18.4
1039	3650	883650	≥1620	≥3.7	≤8.7	≤36.3	≤50.0	29.4
1040	3654	103654	≥2000	≥3.7	≤10.0	≤36.5	≤54.8	36.1
1041	3657	323657	≥750	≥3.7	≤3.2	≤36.0	≤57.5	14.1
1042		403657	≥800	≥3.7	≤4.0	≤36.5	≤57.5	15.0
1043		503657	≥1000	≥3.7	≤5.0	≤36.5	≤57.5	18.6
1044		583657G	≥1250	≥3.7	≤5.8	≤36.5	≤59.5	23.0
1045	3674	253674	≥600	≥3.7	≤2.8	≤36.0	≤73.5	11.7
1046	3679	623679	≥2000	≥3.7	≤6.2	≤36.0	≤79.0	36.3
1047	3686	473686	≥1550	≥3.7	≤4.5	≤36.5	≤86.5	28.6
1048	3736	653736HV	≥1100	≥3.8	≤6.5	≤36.5	≤35.5	20.2
1049	3737	433737G	≥600	≥3.7	≤4.4	≤38.0	≤37.5	11.2
1050	3739	433739	≥650	≥3.7	≤4.3	≤37.5	≤39.5	12.1
1051		483739	≥720	≥3.7	≤5.0	≤37.5	≤39.5	13.3
1052		603739P	≥750	≥3.7	≤6.1	≤37.5	≤39.5	13.9
1053		253740	≥400	≥3.7	≤2.6	≤37.0	≤39.5	7.7
1054	3746	283846	≥400	≥3.7	≤2.7	≤38.0	≤46.3	7.8
1055		383746	≥740	≥3.7	≤3.8	≤37.5	≤46.3	13.8
1056	3751	763751	≥1580	≥3.7	≤7.6	≤37.5	≤51.0	28.7
1057		903751	≥1900	≥3.7	≤9.0	≤37.5	≤51.5	34.3
1058	3756	423756G	≥920	≥3.7	≤4.2	≤37.4	≤56.5	17.1
1059		483756G	≥1100	≥3.7	≤4.8	≤37.0	≤56.0	20.3
1060		603756	≥1350	≥3.7	≤6.2	≤37.5	≤56.0	24.7
1061	3757	513757	≥1200	≥3.7	≤5.1	≤37.0	≤59.5	22.1
1062	3759	303759	≥700	≥3.7	≤3.0	≤37.5	≤59.5	13.3
1063		363759	≥830	≥3.7	≤3.6	≤37.5	≤59.5	15.5
1064		403759	≥850	≥3.7	≤4.0	≤37.5	≤59.5	15.9

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
1065	3759	503759	≥1200	≥3.7	≤5.1	≤37.5	≤59.5	22.1
1066		503759M3	≥1000	≥3.7	≤5.0	≤37.5	≤59.5	18.6
1067		523759	≥1220	≥3.7	≤5.2	≤37.5	≤59.5	22.5
1068		533759	≥1250	≥3.7	≤5.3	≤37.5	≤59.5	23.0
1069		543759	≥1300	≥3.7	≤5.2	≤37.3	≤59.5	23.9
1070		553759	≥1350	≥3.7	≤5.5	≤37.5	≤59.5	24.8
1071		583759	≥1400	≥3.7	≤6.0	≤37.5	≤59.5	25.6
1072		603739P	≥750	≥3.7	≤6.1	≤37.5	≤39.5	13.9
1073		603759	≥1500	≥3.7	≤6.4	≤37.5	≤59.8	27.4
1074		623759	≥1500	≥3.7	≤6.2	≤37.5	≤59.8	27.4
1075		783759	≥1800	≥3.7	≤7.8	≤37.5	≤60.5	32.7
1076		903759	≥2200	≥3.7	≤9.2	≤37.5	≤59.5	39.7
1077		953759	≥2200	≥3.7	≤9.7	≤37.5	≤59.5	39.7
1078		103759	≥2500	≥3.7	≤10	≤37.5	≤60	40.4
1079		37107	4837107	≥2000	≥3.7	≤4.8	≤37.5	≤107.5
1080	6037107		≥2500	≥3.7	≤6.2	≤37.5	≤107.5	25.6
1081	37110	4037110	≥1800	≥3.7	≤4.2	≤37.5	≤108.5	33.3
1082		5537110	≥2200	≥3.7	≤5.5	≤37.0	≤108.5	40.3
1083	3840	383840	≥530	≥3.7	≤3.9	≤38.5	≤39.0	10.0
1084		433840	≥630	≥3.7	≤4.4	≤38.5	≤40.0	11.8
1085	3842	423842	≥650	≥3.7	≤4.4	≤38.5	≤42.5	12.2
1086	3848	713848	≥1400	≥3.7	≤7.1	≤38.5	≤48.8	25.5
1087		813848	≥1730	≥3.7	≤8.1	≤38.5	≤48.5	31.3
1088		903848	≥1700	≥3.7	≤8.9	≤38.5	≤48.5	30.8
1089	3860	683860	≥1750	≥3.7	≤6.8	≤38.5	≤60.8	31.8
1090		703860	≥1800	≥3.7	≤7.0	≤38.5	≤60.5	32.7
1091		723860	≥1800	≥3.7	≤7.5	≤38.5	≤60.5	32.7
1092	3870	703860	≥1500	≥3.7	≤5	≤38.5	≤70.0	27.5
1093	3943	303943	≥480	≥3.7	≤3.1	≤39.0	≤43.5	9.2
1094		503943	≥800	≥3.7	≤5.2	≤39.5	≤43.0	14.8
1095		703943	≥1300	≥3.7	≤7.0	≤39.5	≤43.0	23.8
1096	3944	603944	≥1100	≥3.7	≤5.9	≤39.0	≤46.0	20.2
1097		703944G	≥1350	≥3.7	≤7.1	≤39.8	≤45.3	24.7
1098	3947	393547	≥700	≥3.7	≤3.45	≤39.3	≤47.5	13.1
1099		483947	≥880	≥3.7	≤4.8	≤39.5	≤47.5	16.3
1100		533947	≥1050	≥3.7	≤5.3	≤39.5	≤47.5	19.4
1101		973947	≥2000	≥3.7	≤9.7	≤39.5	≤48.0	36.1
1102	3982	403982G	≥1400	≥3.7	≤4.0	≤39.5	≤82.0	26.0



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
1103	4041	314043HV	≥600	≥3.8	≤3.1	≤39.5	≤43.5	11.3
1104		434041	≥650	≥3.7	4.3	40.5	41.5	12.2
1105		604043	≥1150	≥3.7	≤5.8	≤40.0	≤44.0	21.1
1106		614041	≥1050	≥3.7	≤6.1	≤40.3	≤41.0	19.3
1107		734041	≥1250	≥3.7	≤7.3	≤40.0	≤41.0	22.9
1108		104041	≥1600	≥3.7	≤10.0	≤40.0	≤41.0	29.0
1109	4050	504050	≥1170	≥3.7	≤5.08	≤40	≤50.5	21.5
1110		684050	≥1500	≥3.7	≤6.8	≤40.5	≤50.5	27.4
1111		704050	≥1500	≥3.7	≤7.1	≤40.3	≤50.3	27.3
1112		784050D	≥1800	≥3.7	≤7.85	≤40.5	≤50.0	32.6
1113		854050	≥2000	≥3.7	≤8.5	≤40.5	≤50.7	36.1
1114		984050D	≥2300	≥3.7	≤9.8	≤40.5	≤50.5	41.4
1115	104050	≥2200	≥3.7	≤10.1	≤40.5	≤50.5	39.7	
1116	4052	304052	≥680	≥3.7	≤3.0	≤40.5	≤52.5	12.9
1117		384052	≥820	≥3.7	≤3.8	≤40.5	≤52.5	15.3
1118		554052M3	≥1100	≥3.7	≤5.5	≤40.5	≤52.5	20.3
1119	4053	604053M3	≥1000	≥3.7	≤6.0	≤40.5	≤53.5	18.6
1120		604053	≥1400	≥3.7	≤6.2	≤40.5	≤53.5	25.6
1121		604053P	≥1100	≥3.7	≤6.0	≤40.5	≤53.5	20.4
1122		854053M3	≥1600	≥3.7	≤8.2	≤40.5	≤53.5	29.1
1123	4055	694055G	≥1800	≥3.7	≤6.9	≤41	≤55.5	32.7
1124	4057	504057	≥1200	≥3.7	≤4.9	≤40.5	≤57.0	22.2
1125		104057DN1	≥2700	≥3.7	≤10.0	≤40.3	≤57.0	48.5
1126	4068	484068	≥1400	≥3.7	≤4.8	≤40.3	≤69.5	25.8
1127		504068	≥1450	≥3.7	≤5.0	≤40.3	≤69.5	26.7
1128	4069	404069	≥1200	≥3.7	≤4.0	≤41.0	≤70.0	22.4
1129		604069	≥2000	≥3.7	≤6.0	≤40.0	≤69.5	36.3
1130		794069	≥2600	≥3.7	≤7.9	≤40.0	≤70.0	46.8
1131		824069	≥2600	≥3.7	≤8.1	≤40.4	≤69.8	46.8
1132	4086	454086	≥1750	≥3.7	≤4.5	≤40.0	≤86.0	32.2
1133		504086	≥2000	≥3.7	≤5.0	≤40.0	≤85.0	36.5
1134	4139	524150D	≥1475	≥3.7	≤5.2	≤41	≤50	26.9
1135		764139	≥1200	≥3.7	≤7.6	≤41.0	≤39.5	22.0
1136	4155	724155	≥1680	≥3.7	≤7.2	≤41.5	≤55.5	30.6
1137		754155	≥1750	≥3.7	≤7.5	≤41.5	≤55.5	31.8
1138	4166	654166	≥2000	≥3.7	≤6.5	≤41.5	≤66.0	36.3
1139		854166	≥2600	≥3.7	≤8.6	≤41.5	≤66.5	46.8
1140	4167	604167	≥1800	≥3.7	≤6.2	≤41.0	≤67.5	32.8

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
1141	4167	104167N	≥3000	≥3.7	≤10.0	≤41.0	≤67.0	53.8
1142	4169	454169	≥1300	≥3.7	≤4.5	≤41.5	≤70.0	24.1
1143		504169G	≥1450	≥3.7	≤5.0	≤41.5	≤69.5	26.7
1144		554169G	≥1800	≥3.7	≤5.5	≤41.5	≤69.5	32.9
1145		654169	≥2000	≥3.7	≤6.5	≤41.5	≤69.5	36.4
1146		754169	≥2200	≥3.7	≤7.5	≤41.5	≤69.5	39.9
1147		884169	≥3000	≥3.7	≤8.8	≤41.5	≤69.5	53.8
1148		114169M1	≥3500	≥3.7	≤11.0	≤41.5	≤69.5	62.6
1149		4173	304173	≥800	≥3.7	≤2.95	≤40.8	≤73.5
1150	4242	104242	≥1750	≥3.7	≤10.2	≤42.3	≤41.0	31.7
1151	4250	524150D	≥1475	≥3.7	≤5.2	≤41.0	≤49.0	26.9
1152		834250M3	≥1500	≥3.7	≤8.3	≤42.0	≤50.5	27.4
1153		864250M3	≥1650	≥3.7	≤8.6	≤42.5	≤50.5	30.0
1154	4260	384260	≥1150	≥3.7	≤3.8	≤42.5	≤60.5	21.4
1155		454260	≥1300	≥3.7	≤4.5	≤42.5	≤60.5	24.0
1156		564260	≥1650	≥3.7	≤5.4	≤42.0	≤62.3	30.1
1157		804260	≥2300	≥3.7	≤8.2	≤42.0	≤60.5	41.5
1158		944261	≥3000	≥3.7	≤9.4	≤42.0	≤60.5	53.8
1159		104260	≥2600	≥3.7	≤10.0	≤42.5	≤60.5	46.8
1160	4261	454261HV	≥1500	≥3.8	≤4.6	≤42.5	≤60.8	27.5
1161	4268	824270	≥2800	≥3.7	≤8.3	≤42.5	≤69.0	50.4
1162		864268	≥3000	≥3.7	≤8.6	≤42.5	≤68.5	53.9
1163	4275	854275	≥3100	≥3.7	≤8.7	≤42.0	≤75.5	55.7
1164		114275	≥4000	≥3.7	≤11.0	≤42.0	≤75.0	71.4
1165	4289	384289	≥1450	≥3.7	≤4.0	≤42.5	≤89.5	27.1
1166		504289	≥2100	≥3.7	≤5.0	≤42.5	≤89.5	38.4
1167		564289	≥2500	≥3.7	≤5.6	≤42.5	≤89.5	45.4
1168	42113	6842113	≥3600	≥3.7	≤6.8	≤42.5	≤113.5	71.2
1169	4355	404355G	≥950	≥3.7	≤4.0	≤43.0	≤55.5	17.7
1170		684355	≥1750	≥3.7	≤6.8	≤43.5	≤55.8	31.9
1171	4357	804357	≥2200	≥3.7	≤8.0	≤43.5	≤57.8	39.8
1172	4359	534359	≥1450	≥3.7	≤5.3	≤44.0	≤60.0	26.7
1173		674360G	≥1950	≥3.7	≤6.7	≤43.5	≤60.5	35.4
1174		804359G	≥2200	≥3.7	≤8.2	≤43.8	≤59.8	39.8
1175	4360	624360M4	≥1500	≥3.7	≤6.2	≤43.5	≤60.5	27.5
1176		674360	≥1950	≥3.7	≤6.7	≤43.5	≤60.5	35.4
1177		674360M	≥1350	≥3.7	≤6.7	≤43.5	≤60.5	24.9
1178		854360G	≥2350	≥3.7	≤8.5	≤43.5	≤60.5	42.4

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**

Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
1179	4370	824370	≥2800	≥3.7	≤8.3	≤44.0	≤71.0	50.4
1180	4375	803475	≥2200	≥3.7	≤8.0	≤34.5	≤75.0	39.7
1181	754380	304380	≥1180	≥3.7	≤3.00	≤43.3	≤80.5	22.2
1182	4388	804388	≥3480	≥3.7	≤7.9	≤43.0	≤88.5	62.5
1183	4441	654441	≥1400	≥3.7	≤6.5	≤44.0	≤41.5	25.6
1184	4450	604450	≥1500	≥3.7	≤6.0	≤44.5	≤50.5	27.4
1185		704450	≥1700	≥3.7	≤7.0	≤44.5	≤51.0	30.9
1186		754450D	≥1800	≥3.7	≤7.5	≤44.3	≤51.0	32.7
1187		854450	≥2000	≥3.7	≤8.5	≤44.5	≤50.8	36.2
1188		904450	≥2200	≥3.7	≤9.0	≤44.5	≤50.8	39.7
1189		954450	≥2200	≥3.7	≤9.5	≤44.5	≤50.8	39.7
1190		104450P	≥2000	≥3.7	≤10.0	≤44.5	≤50.8	36.2
1191		114450	≥2500	≥3.7	≤11.2	≤44.5	≤50.8	45.0
1192	4455	374455	≥1000	≥3.7	≤3.9	≤44.5	≤55.5	18.7
1193		564455P	≥1400	≥3.7	≤5.8	≤44.5	≤56.0	25.7
1194	4460	704460HG	≥2170	≥3.7	≤7	≤44.5	≤60.0	39.3
1195	4472	804472	≥2800	≥3.7	≤8.1	≤44.5	≤72.5	50.5
1196	4561	274561HV	≥900	≥3.7	≤2.75	≤45.5	≤61.5	17.0
1197		334561	≥900	≥3.7	≤3.3	≤45.5	≤61.5	17.0
1198		334561G	≥900	≥3.7	≤3.3	≤45.5	≤61.5	17.0
1199		524561	≥1700	≥3.7	≤5.2	≤45.2	≤61.8	31.1
1200		604561	≥2000	≥3.7	≤6.0	≤45.5	≤61.8	36.4
1201		904561	≥2750	≥3.7	≤9.0	≤45.5	≤62.0	49.5
1202	4654	404674	≥1800	≥3.7	≤4.1	≤46.5	≤74.0	33.1
1203		504654	≥1500	≥3.7	≤5.2	≤46.5	≤54.5	27.5
1204		504654L	≥1400	≥3.7	≤5.0	≤46.5	≤54.5	25.8
1205		534664D	≥1750	≥3.7	≤5.3	≤46.0	≤64.0	32.0
1206		724654	≥1950	≥3.7	≤7.2	≤46.5	≤54.5	35.4
1207		764654	≥2200	≥3.7	≤7.6	≤46.5	≤54.8	39.8
1208		804654	≥2200	≥3.7	≤8.2	≤46.5	≤54.8	39.8
1209	4699	604699M3	≥2850	≥3.7	≤6.0	≤46.5	≤99.0	51.8
1210	46102	4546102	≥2500	≥3.7	≤4.7	≤46.5	≤102.5	39.3
1211	46146	4546146	≥3400	≥3.7	≤4.6	≤46.0	≤146.0	60.9
1212	4740	534740	≥1000	≥3.7	≤5.3	≤47.8	≤40.0	18.6
1213	4759	774759	≥2700	≥3.7	≤7.7	≤47	≤59.5	48.6
1214		854759	≥2500	≥3.7	≤8.5	≤47.0	≤59.5	45.1
1215		914759	≥2900	≥3.7	≤9.1	≤47	≤59.5	52.1
1216	4761	604761	≥1900	≥3.7	≤6.0	≤47.0	≤61.0	34.6



2019 Lithium Polymer Cell Selection Guide

509 East Ellis Road, Norton Shores, MI 49441 U.S.A.

Toll Free No. 1-800-798-7740

ISO 13485

Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
1217	4761	674761	≥2200	≥3.7	≤7.0	≤47.0	≤61.0	39.9
1218		704761	≥2300	≥3.7	≤7.2	≤47.0	≤61.0	41.6
1219		744761	≥2500	≥3.7	≤7.4	≤47.5	≤61.8	45.2
1220	4763	704763	≥2300	≥3.7	≤7.2	≤47.5	≤63.8	41.7
1221		884763	≥3000	≥3.7	≤8.8	≤47.5	≤64.0	53.9
1222	4771	474771	≥1700	≥3.7	≤4.7	≤47.5	≤71.5	31.3
1223		964771	≥3800	≥3.7	≤9.6	≤47.5	≤72.0	68.0
1224	4775	854775	≥3900	≥3.7	≤8.5	≤48.0	≤75.5	69.8
1225		104775	≥4400	≥3.7	≤10.0	≤47.0	≤75.2	78.5
1226	47109	3447109N	≥1750	≥3.7	≤3.35	≤47.3	≤109.5	32.9
1227		4747109	≥2950	≥3.7	≤4.75	≤47.5	≤109.5	114.7
1228		6047109	≥3800	≥3.7	≤6.2	≤47.5	≤109.5	147.7
1229		8047109	≥5000	≥3.7	≤8.0	≤47.0	≤109.5	194.2
1230		8647109M3	≥5000	≥3.7	≤8.6	≤47.5	≤109.5	194.2
1231	4856	304856	≥700	≥3.7	≤2.88	≤46.5	≤57.0	13.4
1232		554856	≥1500	≥3.7	≤5.5	≤46.5	≤55.0	27.5
1233		784856	≥2200	≥3.7	≤7.8	≤49.0	≤57.0	39.9
1234		794856	≥2250	≥3.7	≤7.9	≤49.0	≤57.0	40.8
1235	4858	554856B	≥2000	≥3.7	≤5.25	≤47.5	≤58.5	36.4
1236	4860	334860	≥950	≥3.7	≤3.3	≤48.0	≤60.5	17.9
1237		784860	≥2400	≥3.7	≤7.8	≤48.5	≤60.5	43.4
1238		784860N	≥2400	≥3.7	≤8.0	≤48.5	≤60.5	43.4
1239		824860	≥2800	≥3.7	≤8.6	≤48.5	≤60.5	50.4
1240		904860	≥3000	≥3.7	≤9.0	≤48.3	≤60.5	53.9
1241	4872	364872	≥1350	≥3.7	≤3.8	≤48.0	≤72.5	25.2
1242		464872	≥1800	≥3.7	≤4.7	≤48.0	≤72.0	33.1
1243	4961	514961	≥1800	≥3.7	≤5.1	≤49.1	≤61.5	32.9
1244	4965	404965	≥1450	≥3.7	≤4.0	≤49.5	≤65.5	26.9
1245		454965	≥1600	≥3.7	≤4.45	≤49	≤64.5	29.5
1246		504965	≥1800	≥3.7	≤5.0	≤49.0	≤65.0	33.0
1247		654965	≥2250	≥3.7	≤6.5	≤49.0	≤65.0	40.9
1248	4983	584983	≥2800	≥3.7	≤5.8	≤49.0	≤83.5	50.8
1249		954983N2	≥4700	≥3.7	≤9.6	≤49.5	≤83.8	83.9
1250	5048	305048	≥620	≥3.7	≤2.95	≤49.8	≤48.5	11.9
1251		605048	≥1600	≥3.7	≤6.0	≤50.0	≤48.5	29.3
1252		705048	≥2000	≥3.7	≤7.2	≤50.0	≤48.5	36.3
1253	5056	535056	≥1500	≥3.7	≤5.3	≤50.5	≤56.5	27.6
1254		605056	≥2000	≥3.7	≤6.0	≤50.5	≤56.5	36.4

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
1255	5056	655056	≥1900	≥3.7	≤6.5	≤50.5	≤56.5	34.6
1256		685056	≥2100	≥3.7	≤6.8	≤50.5	≤56.5	38.2
1257		885056G	≥2700	≥3.7	≤8.8	≤50.3	≤57.0	48.7
1258		955056	≥2750	≥3.7	≤9.5	≤50.3	≤55.5	49.5
1259	5058	285058	≥800	≥3.7	≤2.8	≤50.0	≤58.0	15.3
1260	5060	605060	≥2000	≥3.7	≤6	≤50.5	≤60.5	36.5
1261	5068	425068	≥1550	≥3.7	≤4.2	≤50.5	≤68.0	28.7
1262		485068	≥1800	≥3.7	≤4.8	≤50.5	≤68.5	33.1
1263		495068	≥1550	≥3.7	≤5.0	≤50.5	≤68.0	28.7
1264		505068	≥1850	≥3.7	≤5.0	≤50.0	≤68.0	33.9
1265		555068	≥2000	≥3.7	≤5.6	≤50.5	≤68.5	36.6
1266		805068m2	≥3000	≥3.7	≤8.2	≤50.5	≤68.5	54.1
1267		105068	≥3900	≥3.7	≤10.0	≤50.5	≤68.5	69.8
1268		105068P	≥3000	≥3.7	≤10.2	≤50.5	≤68.5	54.1
1269	5080	385080G	≥1600	≥3.7	≤3.8	≤50.5	≤80.5	29.8
1270		505080	≥2200	≥3.7	≤5.0	≤50.5	≤80.5	40.3
1271		725080	≥3500	≥3.7	≤7.2	≤50	≤80.8	63.0
1272		785080	≥3950	≥3.7	≤7.8	≤50.0	≤80.0	70.8
1273	5081	655081	≥3200	≥3.7	≤6.5	≤50.5	≤81.5	57.8
1274	5082	395082	≥1820	≥3.7	≤3.9	≤50.0	≤83.0	33.7
1275	5085	285085	≥1200	≥3.7	≤2.8	≤50.5	≤85.5	22.9
1276		325085	≥1500	≥3.7	≤3.2	≤50.5	≤85.5	28.1
1277		425085	≥2000	≥3.7	≤4.2	≤50.3	≤85.5	36.9
1278		435085	≥2000	≥3.7	≤4.4	≤50.5	≤85.5	36.9
1279		455085	≥2100	≥3.7	≤4.7	≤50.5	≤85.5	38.6
1280		485085	≥2450	≥3.7	≤4.8	≤50.5	≤85.5	44.7
1281		505085	≥2400	≥3.7	≤5.0	≤50.5	≤85.5	43.9
1282		525085	≥2600	≥3.7	≤5.5	≤50.5	≤85.5	47.3
1283		605085	≥3000	≥3.7	≤6.6	≤50.5	≤85.5	54.3
1284		625085	≥2900	≥3.7	≤6.2	≤50.5	≤85.5	52.6
1285		685085	≥3000	≥3.7	≤6.8	≤50.5	≤85.5	54.3
1286		705085	≥3400	≥3.7	≤7.2	≤50.5	≤85.5	61.3
1287		725085	≥3700	≥3.7	≤7.2	≤50.5	≤85.5	66.5
1288		805085M2	≥3800	≥3.7	≤8.0	≤50.5	≤85.5	68.3
1289		855085M	≥4100	≥3.7	≤8.7	≤50.8	≤85.5	73.5
1290		855085	≥4000	≥3.7	≤8.5	≤50.3	≤85.0	71.8
1291		885085	≥4200	≥3.7	≤8.8	≤50.5	≤85.5	75.3
1292		955085M1	≥4800	≥3.7	≤9.8	≤50.5	≤85.5	85.7

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



2019 Lithium Polymer Cell Selection Guide

509 East Ellis Road, Norton Shores, MI 49441 U.S.A.

Toll Free No. 1-800-798-7740

ISO 13485

Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
1293	5085	105085	≥5000	≥3.7	≤10.0	≤50.5	≤85.5	89.2
1294	5098	675098N	≥4000	≥3.7	≤6.7	≤50	≤98	72.0
1295	50112	5350112	≥3350	≥3.7	≤5.5	≤50.5	≤112.5	68.6
1296	5158	585158	≥1950	≥3.7	≤5.8	≤51.5	≤58.0	35.6
1297	5161	555161	≥2000	≥3.7	≤5.5	≤51.5	≤61.5	36.5
1298		655161	≥2500	≥3.7	≤6.4	≤51.0	≤61.0	45.2
1299		725161	≥2500	≥3.7	≤7.2	≤51.0	≤61.5	45.2
1300		105161	≥3600	≥3.7	≤9.9	≤51.0	≤61.5	64.5
1301	5171	235471B	≥800	≥3.7	≤2.3	≤54.7	≤71.0	15.7
1302	5262	535262	≥1700	≥3.7	≤5.3	≤52.5	≤62.5	31.3
1303		555262	≥1850	≥3.7	≤5.5	≤52.5	≤62.5	33.9
1304		755262	≥2500	≥3.7	≤7.5	≤52.0	≤62.0	45.3
1305	5264	805264	≥3250	≥3.7	≤8.0	≤52.0	≤64.5	58.4
1306	5278	405278	≥1900	≥3.7	≤4.2	≤52.5	≤78.5	35.1
1307	52101	3552101	≥2000	≥3.7	≤3.5	≤52.5	≤101.8	31.7
1308		5252101	≥3000	≥3.7	≤5.8	≤52.0	≤101.5	47.7
1309		5852101	≥3200	≥3.7	≤5.8	≤52.0	≤101.5	50.9
1310	5353	605353	≥1900	≥3.7	≤6.0	≤53.5	≤53.5	34.7
1311	5365	395365HV	≥1700	≥3.8	≤3.9	≤53.0	≤65.0	31.3
1312		505365	≥2000	≥3.7	≤5	≤53.2	≤65.5	36.6
1313		505365	≥2800	≥3.7	≤5.5	≤53.8	≤74.0	50.7
1314	5374	505374	≥2600	≥3.7	≤5.0	≤53.8	≤74.0	47.2
1315	5457	445457	≥1500	≥3.7	≤4.4	≤54.5	≤57.5	27.7
1316	5462	555462	≥2000	≥3.7	≤5.5	≤54.0	≤62.5	36.6
1317		705462	≥2580	≥3.7	≤7.0	≤54.0	≤62.0	46.7
1318		785462	≥2800	≥3.7	≤7.8	≤54.5	≤62.8	50.6
1319		805462	≥3000	≥3.7	≤8.2	≤54.0	≤62.0	54.1
1320		905462	≥3250	≥3.7	≤8.9	≤53.5	≤62.5	58.4
1321	5471	235471	≥800	≥3.7	≤2.3	≤53.8	≤71.0	15.6
1322	5473	605473P	≥2600	≥3.7	≤6	≤54.5	≤73.0	47.2
1323	5475	545675	≥2600	≥3.7	≤5	≤53.8	≤73.0	47.2
1324	5486	405486	≥2200	≥3.7	≤4.0	≤54.3	≤86.5	40.5
1325		505486	≥2900	≥3.7	≤5.0	≤54.5	≤86.5	52.7
1326		555486	≥3000	≥3.7	≤5.5	≤54.5	≤86.5	54.5
1327		905486M4	≥4100	≥3.7	≤9.0	≤55.0	≤87.0	73.7
1328	5545	455545	≥1200	≥3.7	≤4.7	≤55.5	≤45.5	22.3
1329	5570	885570	≥3900	≥3.7	≤9.0	≤55.5	≤70.0	70.0
1330		905570M1	≥4000	≥3.7	≤9.2	≤55.5	≤70.5	71.7

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



2019 Lithium Polymer Cell Selection Guide

509 East Ellis Road, Norton Shores, MI 49441 U.S.A.

Toll Free No. 1-800-798-7740

ISO 13485

Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
1331	5590	325590	≥1900	≥3.7	≤3.25	≤55.5	≤90.5	35.4
1332		655590	≥4000	≥3.7	≤6.45	≤55.3	≤90.8	72.0
1333		105590	≥6000	≥3.7	≤10.0	≤55.5	≤90.8	106.9
1334	5659	655659	≥2600	≥3.7	≤6.5	≤56.0	≤59.0	47.1
1335	5686	855686	≥5500	≥3.7	≤8.5	≤56.5	≤86.0	98.2
1336	5712	3057123	≥2300	≥3.7	≤3.1	≤58.0	≤124.0	42.1
1337	5770	355770	≥1600	≥3.7	≤3.7	≤57.5	≤70.5	29.8
1338	5784	555784	≥2950	≥3.7	≤5.5	≤57.7	≤84.0	53.7
1339	58110	6558110M3	≥4200	≥3.7	≤6.6	≤59.0	≤110.5	103.1
1340		7258110	≥5500	≥3.7	≤7.2	≤58.0	≤111.0	125.1
1341		8058110	≥6500	≥3.7	≤8.2	≤58.5	≤110.5	159.4
1342	5948	495948	≥1600	≥3.7	≤4.9	≤59.8	≤48.0	29.4
1343	5996	405996	≥2650	≥3.7	≤3.9	≤58.8	≤94.0	48.7
1344	6087	346087	≥2100	≥3.7	≤3.4	≤60.5	≤87.0	39.0
1345		606087	≥3800	≥3.7	≤6.0	≤60.0	≤87.0	68.6
1346	6091	456091	≥3000	≥3.7	≤4.7	≤60.5	≤91.5	54.8
1347		506091	≥3200	≥3.7	≤5.0	≤60.5	≤91.5	58.3
1348		676091M2	≥4000	≥3.7	≤6.7	≤60.5	≤91.5	72.2
1349		726091	≥5000	≥3.7	≤7.2	≤60	≤91.5	89.6
1350		776091M1	≥5000	≥3.7	≤7.7	≤60.5	≤91.5	89.7
1352	6159	816159N3	≥3000	≥3.7	≤8.1	≤61.5	≤59.0	54.2
1353	6162	546162	≥2500	≥3.7	≤5.45	≤61.0	≤62.0	45.5
1354	62107	4562107M3	≥3000	≥3.7	≤4.5	≤61.0	≤107.0	36.1
1355		5062107	≥3800	≥3.7	≤5.0	≤62.0	≤107.0	69.1
1356		5662107	≥5000	≥3.7	≤5.6	≤61.5	≤107.0	90.0
1357	63133	3763133M2	≥3400	≥3.7	≤3.7	≤63.0	≤133.0	61.3
1358	6478	486478	≥2500	≥3.7	≤5.0	≤64.5	≤78.5	45.9
1359		566478M1	≥3000	≥3.7	≤5.6	≤64.5	≤78.5	54.6
1360		606478	≥3000	≥3.7	≤6.0	≤64.5	≤78.5	54.6
1361	6570	656570P	≥3100	≥3.7	≤6.6	≤65.5	≤70.5	56.2
1362		966570M1	≥5000	≥3.7	≤9.6	≤65.0	≤70.5	89.5
1363	6573	366573	≥1800	≥3.7	≤3.6	≤65.5	≤73.5	33.6
1364	6576	906576M3	≥4700	≥3.7	≤9.2	≤65.5	≤76.5	84.3
1365		956576M3	≥5000	≥3.7	≤9.5	≤65.5	≤76.5	89.6
1366	6585	856585m3	≥5200	≥3.7	≤8.5	≤65.0	≤85.0	93.2
1367		896585	≥5600	≥3.7	≤8.9	≤65.0	≤85.5	100.2
1368	7390	487390	≥3650	≥3.7	≤5.0	≤73.8	≤90.0	66.5
1369		487390L	≥3500	≥3.7	≤5.0	≤73.8	≤90.0	63.9

**Dimensions listed are for cell only, does not include PCM or multiple cell configurations.
Please request verification of dimensions to meet design requirements**



509 East Ellis Road, Norton Shores, MI 49441 U.S.A.

Toll Free No. 1-800-798-7740

ISO 13485

Number	Series	Model	Capacity (mAh)	Voltage (V)	Thickness (mm)	Width (mm)	Length (mm)	Weight (g)
1370	7535	527535G	≥1300	≥3.7	≤5.3	≤75.5	≤35.5	24.2
1371	7595	407595	≥2850	≥3.7	≤4.0	≤75.5	≤95.5	52.8
1372	7696	407696M1	≥3300	≥3.7	≤4.0	≤76.0	≤96.5	60.7